

Termékkód	Leírás	Listaár
Switchers		
Datavideo SE-500HD	The datavideo SE-500HD is a small, cost-effective, HD/SD digital video switcher with easy-to-use professional features. It offers 4 HDMI inputs and 2 HDMI outputs, support video formats up to Full HD 1080P, an audio mixer with microphone and unbalance RCA audio inputs, RCA audio outputs, more features including Luma Keyer, PIP, WIPE Generator and Tally.	289 440 Ft
Datavideo SE-650	4 Input Digital Video Switcher (Unibody), easy to learn and use. Includes 2 HD-SDI and 2 HDMI Inputs, 2 RCA Inputs for audio embedding with audio mixing feature. Built-in multiviewer, Supporting Linear/Luma Key, Wipe, Mix & Cut Transitions, 1 DSK, Full M/E Preview function, Frame store, Dedicated Stills Buffer for 24 Images. XPT (Cross Point Assignment, Tally output, GPI Output)	315 360 Ft
Datavideo SE-1200MU	6 Input HD Digital Video Switcher (1RU mainunit, GUI as UI) with: 4x HD-SDI and 2x HDMI Inputs each input Synchronised 2x HD-SDI & 2x HDMI Outputs (Can be assigned as PVW/PGM/Clean/MV) 2 Upstream Keyers, supporting Chroma Key & Linear/Luma Key 2 DSK's, 1 PIP, Wipe, Mix & Cut Transitions, Full M/E Preview function, Up to 24 images Still-store, Xpoint assignment, PC/Tablet control, built-in Multiviewer also in MJPEG (streaming) & Tally/GPI, 2 XLR Inputs for audio embedding	396 000 Ft
Datavideo RMC-260	Hardware control panel for SE-1200MU videowitcher (Serial control) AVAILABLE MARCH 2016	131 040 Ft
Datavideo SE-2200	6 Input HD/SD Digital Video Switcher (Splitunit) with: 6x HD-SDI or 4x HD-SDI +2x HDMI Inputs (Synchronised) 6x HD-SDI (XPT/AUX/PVW/PGM), 2x HDMI (Multiviewer only) FTB, Mix, Cut, Wipe effects, 2x PIP & a DSK INCLUDING: Title Creator Software (CG-200) For more info see p.n. 2400-1030 Switcher operation mode HD (1080i / 720P) or SD (576i) switcher	790 560 Ft
Datavideo SE-2200 MU	SE-2200MU: 6 input switcher 19" main unit	658 080 Ft
Datavideo SE-2200 KB	SE-2200KB: control panel for SE-2200 main unit	131 040 Ft
Datavideo SE-2850-8	8 input Digital Video Switcher (Splitunit) with: 1080i/P & 720P inputs, 1080i output signal Frame Sync on each input (genlocked) Built in Multiviewer w clock and counter 2 downstream keyers (Luma&alpha ch.) Wipe/Mix/Cut transitions, Full ME preview, X-point assignment through OSD Built in down scaler, Tally / GPI output, Color keys, Remote control by Ethernet Audio delay on de-embedded output (Expandable to 12 inputs)	1 195 200 Ft
Datavideo SE-2850-12	12 input Digital Video Switcher (Splitunit) with: 1080i/P & 720P inputs, 1080i output signal Frame Sync on each input (genlocked) Built in Multiviewer w clock and counter 2 downstream keyers (Luma&alpha ch.) Wipe/Mix/Cut transitions, Full ME preview, X-point assignment through OSD Built in down scaler, Tally / GPI output, Color keys, Remote control by Ethernet Audio delay on de-embedded output	1 310 400 Ft
Datavideo SE-2850-4-INP	4 input expansion module for SE-2850-8	128 160 Ft

Solid aluminium 19" rack mount holder. Size 2U to hold 1U recorder and 1U Talkback system. Universal use for SE-2000, SE-600 and more.

RKM-2000

79 200 Ft

Tally controlbox for use i.c.w. SE-500 or RMC-90 or SE-2000 (special cable needed) Contains also; 4 x TD-2 tally light, 4x CB-7, 1.2 m Tally cable, 1x 15 pin SUB-D male-female

TB-5

38 880 Ft

Mobile Systems (Case)

Datavideo

HS-1200

Handcarry System, Portable production unit, designed as a suitcase providing; HD/SD Digital video switcher with XPT assignments, FTB, Mix, Cut, Wipe effects, PiP & 2x downstream keyer
Video inputs: 6x HD-SDI or 4x HD-SDI +2x HDMI
Video outputs: 1x HD-SDI & 1x HDMI (XPT/AUX/PVW/PGM)
Tally/GPI output. Built-in 17.3" (1600x900) integrated monitor. (Main power or 12V)
AVAILABLE MARCH 2016

790 560 Ft

Datavideo

HS-2200

Handcarry System, Portable production unit, designed as a suitcase providing; HD/SD Digital video switcher with XPT assignments, FTB, Mix, Cut, Wipe effects, 2x PiP & a downstream keyer
Video inputs: 6x HD-SDI or 4x HD-SDI +2x HDMI
Video outputs: 5x HD-SDI (XPT/AUX/PVW/PGM), 1x HDMI (Multiviewer only)
Built in TC-200 title creator technology and FREE CG-200 software.
For more info see art. 2400-1030

1 454 400 Ft

Mobile Systems (MS-Series)

Datavideo

MS-2850A

The MS-2850 is an all-in-one mobile video studio with foldable 17" FHD monitor, built around the datavideo SE-2850 switcher, the MS-2850 provides superb 10 bit 4:2:2 broadcast quality video. The mobile video studio is a ready to go switcher, it will save a lot of crew time when setting up or breaking down in the field. Owing to a bespoke tally and communication system, the MS-2850 enables you as a producer/director to direct and manage a live production when working with a crew of 8 camera operators. Version A comes with; [SE-2850], [TLM-170L], [ITC-100], [HDR-70], [AD-100M], [PD2A]

3 801 600 Ft

Datavideo

MS-2850B

The MS-2850 is an all-in-one mobile video studio with foldable 17" FHD monitor, built around the datavideo SE-2850 switcher, the MS-2850 provides superb 10 bit 4:2:2 broadcast quality video. The mobile video studio is a ready to go switcher, it will save a lot of crew time when setting up or breaking down in the field. Owing to a bespoke tally and communication system, the MS-2850 enables you as a producer/director to direct and manage a live production when working with a crew of 8 camera operators. Version B comes with; [SE-2850], [TLM-170L], [ITC-100], [HDR-70], [AD-100M], [PD2A], [PD-6], [VSM-100]

4 809 600 Ft

Datavideo

MS-2850C

The MS-2850 is an all-in-one mobile video studio with foldable 17" FHD monitor, built around the datavideo SE-2850 switcher, the MS-2850 provides superb 10 bit 4:2:2 broadcast quality video. The mobile video studio is a ready to go switcher, it will save a lot of crew time when setting up or breaking down in the field. Owing to a bespoke tally and communication system, the MS-2850 enables you as a producer/director to direct and manage a live production when working with a crew of 8 camera operators. Version C comes with; [SE-2850], [TLM-170L], [ITC-100], [HDR-70], [AD-200], [PD-2A]

3 888 000 Ft

Datavideo

MS-2800D

The MS-2850 is an all-in-one mobile video studio with foldable 17" FHD monitor, built around the datavideo SE-2850 switcher, the MS-2850 provides superb 10 bit 4:2:2 broadcast quality video. The mobile video studio is a ready to go switcher, it will save a lot of crew time when setting up or breaking down in the field. Owing to a bespoke tally and communication system, the MS-2850 enables you as a producer/director to direct and manage a live production when working with a crew of 8 camera operators. Version D comes with; [SE-2850], [TLM-170L], [ITC-100], [HDR-70], [AD-200], [PD-2A], [PD-6], [VSM-100]

4 809 600 Ft

Mobile Systems (OBV-Series)

Datavideo

OBV-2850A

HD/SD 8 or 12 Channel Portable production unit (2-racks) including: 1 x SE-2850 8 Channel Digital Video Switcher; 2 x TLM-170LR: HD monitors for multiviewer/PGM; 1 x HDR-70: HD recorders for PGM and AUX; VSM-100: vectorscope / waveform monitor; ITC-100: 8-ch intercom / tally system with 8-Ch belt pack; AM-100: 5-ch audio mixer; AD-100: audio delay box; PD-2A: power distributor (8 x DC 12V); PD-6: 8-ch power center; RP-45: 8-ch CV return video; VP-445: 4-ch SDI amplifier; DAC-50 Digital/Analog converter. (CH 9-12 are optional)

7 401 600 Ft

Datavideo	OBV-2850B	HD/SD 12 Channel Portable production unit (2-racks) including: 1 x SE-2850 12 Channel Digital Video Switcher; 2 x TLM-170LR: HD monitors for multiviewer/PGM; 1 x HDR-70: HD recorders for PGM and AUX; VSM-100: vectorscope / waveform monitor; ITC-100: 8-ch intercom / tally system with 8-Ch belt pack; AM-100: 5-ch audio mixer; AD-100: audio delay box; PD-2A: power distributor (8 x DC 12V); PD-6: 8-ch power center; RP-45: 8-ch CV return video; VP-445: 4-ch SDI amplifier; DAC-50 Digital/Analog converter; KMU-100 2 Channel UHD processing unit with control panel RMC-185	8 726 400 Ft
Datavideo	OBV-2850C	HD/SD 8 or 12 Channel Portable Production Unit with Camera Control (2-racks) including: 1 x SE-2850 8 Channel Digital Video Switcher; 2 x TLM-170LR 3G-SDI LED LCD Monitor; 1 x HDR-70 HD/SD Digital Video Recorder; 1 x VSM-100 Sampling Vector Scope Monitor; 1 x ITC-100 8 Way Intercom Talk Back System; 1 x MCU-200 Multi-Camera Control Unit; 1 x AD-200 Audio Level / Delay Control Panel; 1 x CCU100P / CCU-100S / CCU-100J Camera control unit with complementary AD-2's; 1 x NVS-25 Video Streaming Server; 1 x RP-76 Rear Panel with LAN / HDMI. (CH 9-12 are optional)	9 504 000 Ft
Datavideo	OBV-RACK	19 inch.Rack for use with table which fit SE-900, SE-600, SE-2000, SE-3000 or blank table, Excl. table, mnt height rear 27U.	404 640 Ft
Datavideo	OBV-T900/2800	19 inch foldable Table with cut-out for SE-2800 control panel Can be used with OBV-systems	168 480 Ft
Datavideo	OBV-TB-3000/2000/600	Blank Table for OBV rack which hold SE-3000 control panel. (Also suitable for SE-2000/ SE-600) Depth appr. 48 cm.	174 240 Ft
Datavideo	OBV Trolley	OBV Trolley to be used with OBV systems to move racks easily	64 800 Ft
Datavideo	OBV-TB-BK	19 inch foldable Blank Table (Depth appr. 37,5 cm) Can be used with our OBV-systems	165 600 Ft
	OBV-JP	Joint plate to connect multiple OBV racks together (set of 3 plates)	10 368 Ft
4K Systems			
Datavideo	RMC-185	Remote control console for KMU-100 The RMC-185 is designed for controlling the KMU series products (4K Multizone processor), which includes functions of quad/multiview monitoring, camera movement (Pan/Tilt/Zoom) 4 Main presets are available storing all parameters. Start/Stop/Reset function for pre-defined linear motion paths/channel. A full KMU-100 (2 4K Channel unit) can be controlled with a single RMC-185	249 120 Ft
Datavideo	KMU-100	4K Dual channel multipurpose processing unit providing up/down/cross and scaling functionality Connectivity through HDMI 2.0, DisplayPort, 12G and 4x 3G This unit enables the user to get 4 dynamic "cut-outs" with zoom en motion features whereby each "cut-out" has it's own 3Gbps output (Virtual production with region of interest) Also for large public display purposes this unit can be used to "stitch" multiple displays to one large screen.	1 310 400 Ft
PTZ Camera/Control			

Datavideo	PTC-150 Black	Full HD PTZ camera (Black) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's	666 720 Ft
Datavideo	PTC-150 White	Full HD PTZ camera (White) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's	666 720 Ft
Datavideo	PTC-150T	Full HD PTZ camera (Black) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's & HDBaseT	936 000 Ft
Datavideo	PTC-150TW	Full HD PTZ camera (White) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's & HDBaseT	936 000 Ft
Datavideo	PTC-150TL	Full HD PTZ camera (Black) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's & HDBaseT Built in Green/Red Tally LED Control thru IR/RF Controller/ RS-422/ DVIP Supports SONY VISCA Protocol Supports DVIP Control Protocol (F/W update to activate) With mounting bracket and Flip/Mirror function (& Day/Night function)	802 080 Ft
Datavideo	PTC-150TWL	Full HD PTZ camera (White) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's & HDBaseT Built in Green/Red Tally LED Control thru IR/RF Controller/ RS-422/ DVIP Supports SONY VISCA Protocol Supports DVIP Control Protocol (F/W update to activate) With mounting bracket and Flip/Mirror function (& Day/Night function) Without 48V	802 080 Ft
Datavideo	PTC-200	UHD PTZ Camera with; •UHD Resolution: 1/2.3" High Definition 8.93 M Pixels progressive CMOS sensor •12x optical zoom (f = 3.9 mm to 46.8 mm) •UHD (3,840 x 2,160, UHD): 2160p/29.97, 2160p/25 HD: 1080p/59.94,1080p/50, 1080i/59.94, 1080i/50, 720p/59.94, 720p/50 •Position coordinates report in real time per frame •Video Output: 3G-SDI + HDMI synchronously	828 000 Ft
Datavideo	PTC-200T	UHD PTZ Camera with; •UHD Res.: 1/2.3" High Definition 8.93 M Pixels progressive CMOS sensor •12x optical zoom (f = 3.9 mm to 46.8 mm) •UHD (3,840 x 2,160, UHD): 2160p/29.97, 2160p/25 HD: 1080p/59.94,1080p/50, 1080i/59.94, 1080i/50, 720p/59.94, 720p/50 •Position coordinates report in real time per frame •Video Output: 3G-SDI + HDMI synchronously •HDBaseT connectivity	1 080 000 Ft
Datavideo	RKM-150 BLACK	Wall Mount for PTZ camera Black	53 280 Ft
Datavideo	RKM-150 WHITE	Wall Mount for PTZ camera White	53 280 Ft

CB-55 RJ-45 to RS232 converter		
Datavideo	CB-55	19 872 Ft
CB-57 RS-232 to RJ 45 converter (connect from control panel to Cat 5 Only works with the PTC-120		
Datavideo	CB-57	19 872 Ft
HDBaseT Transmitter Box		
	HBT-10	128 160 Ft
HDBaseT Receiver Box		
Datavideo	HBT-11	128 160 Ft
PTZ Camera Control Unit for up-to 4 Pan,Tilt & Zoom Cameras (PTC-150) Pan,Tilt & Zoom with speed control by large joystick Iris, Focus, Gain, and other functions over Ethernet 50 Presets/camera for position/zoom/focus and video calibration parameters Control thru standard CAT-5/6 cable upto 1000 meter Supports VISCA over RS-422 (point-to-point) Compatible with Datavideo's switcher tally indicators		
Datavideo	RMC-180	249 120 Ft
Camera Control Unit		
MCU 100 is a multiple camera controller for Panasonic Camcorders. Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported Panasonic camera's - AG-HPX255, AG-HPX300, AG-HPX301, AG-HPX302, AG-HPX304, AG-HPX370, AG-HPX371, AG-HPX372, AG-HPX500, AG-HPX502, AG-HPX600, AJ-PX800G, AJ-HDX900, AJ-HPX2700G, AJ-HPX3000		
Datavideo	MCU-100P	537 120 Ft
MCU 100S is a multiple camera controller for Sony Camcorders. Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. 4 units Supported Sony Camera's : PMW EX3, PMW EX350, PMW 300K2, PMW 350K, PMW 320, PMW 400, PMW 510, PMW F5, PDW-F55, HDW-F900R		
Datavideo	MCU-100S	537 120 Ft
MCU 100J is a multiple camera controller for JVC Camcorders. Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported JVC Camera's :GY-HM890U (LANC / PS/2), GY-HM850U (LANC / PS/2), GY-HM650U(LANC), GY-HM600U(LANC), GY-LS300CHU (LANC), GY-HM200U (LANC)		
Datavideo	MCU-100J	537 120 Ft
MCU 200 is a multiple camera controller for Panasonic Camcorders.(Rackmountable, 1RU) Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported Panasonic camera's - AG-HPX500/502 HPX-600(NEW) AG-HPX300 / 301/ 302 / 304 / HPX 371		
Datavideo	MCU-200P	537 120 Ft
MCU 200S is a multiple camera controller for Sony Camcorders.(Rackmountable, 1RU) Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. 4 units Supported Sony Camera's : EX-3, EX350, F55, F5		
Datavideo	MCU-200S	537 120 Ft

Datavideo	MCU-200J	MCU 200J is a multiple camera controller for JVC Camcorders.(Rackmountable, 1RU) Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported JVC Camera's : GY-HM890U /GY-HM850U/GY-HM650U/GY-HM600U/GY-HM200U/GY-LS300CHU	537 120 Ft
Datavideo	CCU-100P	Camera control unit for Panasonic camera's to connect and control 4 camera's, supports; HD/SD SDI video; Return video; viewfinder look back video; Two-way headset intercom; Record and Playback; Shutter speed and degree functions; Iris adjustment; AWB & ABB functions; White Balance A, B and Preset functions Knee & Bars functions; Gain adjustment; Tally, including; Power Supply; Ethernet Port for Remote Control; 4 x AD-2P Multi Transmission Adaptor Box; 4 x RMC-240 Remote Controller; 4x HP-3 headphones	1 339 200 Ft
Datavideo	CCU-100S	Camera control unit for Sony camera's to connect and control 4 camera's, supports; HD/SD SDI video; Return video; viewfinder look back video; Two-way headset intercom; Record and Playback; Shutter speed and degree functions; Iris adjustment; AWB & ABB functions; White Balance A, B and Preset functions Knee & Bars functions; Gain adjustment; Tally, including; Power Supply; Ethernet Port for Remote Control; 4 x AD-2P Multi Transmission Adaptor Box; 4 x RMC-240 Remote Controller; 4x HP-3 headphones	1 339 200 Ft
Datavideo	CCU-100J	Camera control unit for JVC camera's to connect and control 4 camera's, supports; HD/SD SDI video; Return video; viewfinder look back video; Two-way headset intercom; Record and Playback; Shutter speed and degree functions; Iris adjustment; AWB & ABB functions; White Balance A, B and Preset functions Knee & Bars functions; Gain adjustment; Tally, including; Power Supply; Ethernet Port for Remote Control; 4 x AD-2P Multi Transmission Adaptor Box; 4 x RMC-240 Remote Controller; 4x HP-3 headphones	1 339 200 Ft
Datavideo	AD-1P	AD-1P Camera adapter for use with MCU-100/200 -Panasonic (10 pin)	73 440 Ft
Datavideo	AD-1S	AD-1S Camera adapter for use with MCU-100S/200S -Sony (8 pin)	73 440 Ft
Datavideo	AD-1J	AD-1J Camera adapter for use with MCU-100J /200J JVC, (8 pin & LAN-C)	73 440 Ft
Datavideo	AD-2P	Multi transmission adapterbox for Panasonic Camera's	188 640 Ft
Datavideo	AD-2S	Multi transmission adapterbox for Sony Camera's	188 640 Ft
Datavideo	AD-2J	Multi transmission adapterbox for JVC Camera's	188 640 Ft

		Shoulder Mount Rig with; Power supply from V-mount battery; USB port for LED light and Phone charger; Power Input: V-mount battery plate; Power Output: D-Tap Connector; Phone Charger and Light: USB; Dimension: 351.2 x 70 x 200.5mm	
Datavideo	SLD-1		93 600 Ft

		Headset with 5-pin XLR (Spare for AD-2)	
	HP-3		25 632 Ft

		MCU-100&200P/S external T-Bar Box. To be used with Sony camera's only	
Datavideo	RMC-230		105 120 Ft

Recorders

		Standalone (Half, 1RU 19 rackunit) H.264 HD video recorder 1 HDMI input and 1 HDMI output records onto NTFS formatted USB devices File format MP4 (H.264) Supports 3D (top to bottom and side by side)	
Datavideo	HDR-10		142 560 Ft

		Rackmountable DV & HDV Harddrive recorder, with removeable 2.5" HDD (HDD not included) Digital IEEE1394 DV/ HDV input and analogue Cvbs video + RCA audio input Headphone connector. Audiolevel indicators.	
Datavideo	DN-700		427 680 Ft

		Compact Highlight/Events recorder. HD/ SD Harddrive Replay recorder with removable 2.5" SSD drive (SSD not included)	
Datavideo	HDR-10		370 080 Ft

		Remote controller to control up to 4 HDR-10 instant replay recorders Provides a GPI interface for functions such as Switcher trigger for playback T-bar for smooth variable replay speed adjustment Jog/shuttle all at once or independentl search control	
Datavideo	RMC-400		131 040 Ft

		Shuttle Express Jog/Shuttle control to operate HDR-10. FOR FREE DURING INTRODUCTION (1/HDR-10)	
	SH-1		22 752 Ft

		HD/ SD Harddrive desktop recorder with removable 2.5" HDD (SSD/ HDD not included) Video input: HD/ SD-SDI. Time code in- and output. Video output: HD/ SD SDI, HDMI. File System NTFS File formats: .MXF and .MOV Recording format 4:2:2 / Up to a max bitrate of 125 Mbps	
Datavideo	HDR-60		514 080 Ft

		HD/ SD Harddrive recorder with removable 2.5" HDD (SSD/ HDD not included) Video input: HD/SD-SDI, Time code in- and output. Video output: HD/SD SDI, HDMI. File System NTFS File formats: .MXF and .MOV Recording format 4:2:2 / Up to a max. bitrate of 125 Mbps, Rackmountable (1RU)	
Datavideo	HDR-70		514 080 Ft

Field Monitoring - Rec/PB

Datavideo	HRS-30	Field Recorder/Monitor supporting: HD/SD-SDI Input and Output with loop thru and embedded audio support The HRS-30 supports MPEG-II Long-GOP or I-frame only with 4:2:2 sampling Supported file formats: MXF/OP1A, MOV Quicktime Storage by a removable hard drive and compatible with 2.5" HDD & SSD drives. Internal colour bar, Blue only, Audio indicator, Safe area and time code display on a 10.1" built in monitor	571 680 Ft
Datavideo	NVP-20	Network Controllable Media Player Excellent image quality with the H.264 codec supporting:mp4, H.264, mkv, mov, TS Full HD through HDMI Output, also CVBS output is available Ethernet controllable player with control for play next clip, play all clips, loop play all clips, pause, resume and seek also remote upload of playlists is supported Supports NTFS and FAT/FAT32 formatted USB storage	102 240 Ft
Datavideo	BR-01	Aluminium bracket with hotshoe and tripod connector . Can hold two BH-08 for DN-60 and/ or TLM-430	10 368 Ft
Datavideo	SATA-50025	HDD 500 Gb 2.5" Sata drive, 7200 RPM 16 Mb Cache. For HDR-60/70 , DN-600/ 700 etc.	28 512 Ft
	HE-3	Spare harddrive carrier for HDR 60 -70 , DN-600-700 etc. (HDD not included)	12 960 Ft
Datavideo	HE-1 BAG	Spare carry case for HE-1 harddrive carrier.	1 728 Ft
Datavideo	HE-2	Spare SSD carrier for HRS-30	9 504 Ft
Encoders/Decoders/Servers			
Datavideo	NVS-25	Video Streaming Encoder/Server or Recorder with: H.264/AVC codec up to High Profile Level 4.0, GOP structure: IBBP, IPPP and IBP HD/SD-SDI & HDMI & CVBS Input Built in de-interlacer for progressive output DHCP Client, RTSP over TCP/UDP/HTTP with MPEG TS. RTMP, HLS (unicast only) H.264 RECORDING FUNCTION onto USB pen drive (up-to 1TB storage) @max 3Mb/s	205 920 Ft
Datavideo	NVS-30	HD video streaming encoder for Live streaming and Recording HDMI in- and outputs Up to 20Mbps streaming and up to 30Mbps recording H.264 RTSP/RTMP streaming and H.264 (MP4) recording Multi-Tap 10 bit scaler and de-interlacer In system Web GUI for control	257 760 Ft
Datavideo	NVS-40	4 Channel HDMI input encoder, 2 streams/ channel. Up to 20Mb/channel with insystem GUI and program output (Quad split)	465 120 Ft

Datavideo	NVD-25	Low Latency IP Video Decoder with: H.264 decoding, RTP/RTSP, RTMP, UDP, TCP, HTTP, HLS and MPEG-TS SDI and Composite video Outputs Simultaneous digital embedded and analogue audio Output Channellist download from DV Stream Server Pro Channel select and volume control	168 480 Ft
Datavideo	NVD-30	NVD-30 is a H.264 stream decoder that works in various ways. It can decode a pointto-(multi)point stream from any streaming platform, it can decode Youtube/Vimeo/Other CDN videos and it can function as a set-top-box for an IPTV network. HDMI output.	122 400 Ft
Datavideo	NVD-35	NVD-35 is a H.264 stream decoder that works in various ways. It can decode a pointto-(multi)point stream from any streaming platform, it can decode Youtube/Vimeo/Other CDN videos and it can function as a set-top-box for an IPTV network. SDI output.	168 480 Ft
Datavideo	DVS-200	DVS-200 is a revolutionary streaming platform allowing the user to encode, transcode, record and deliver real time video to multiple devices. DVS-200 enables you to create an IPTV network, ISO recording and content delivery	205 920 Ft
Prompters			
Datavideo	DVP-100	Wireless teleprompting system to centrally control and synchronise multiple prompter screens through a dedicated WiFi hotspot. (iOS App: DVPrompter Pro) Not yet available for Android. UP to 6 devices can be controlled simultaneously. Controller can create and load new scripts., control the scrolling and perform live edits on all prompter screens in real time. All scripts and settings are stored on the dv prompter server. built in Dualband WiFi.	128 160 Ft
Datavideo	TP-150	Teleprompter, undercamera prompter for use with PTZ camera's holds most tablets even up to iPad pro (large version), available May 2016	38 880 Ft
Datavideo	TP-300	TP-300 Universal Prompter suitable for most camcorders and Tablets from 7" -10" W/O REMOTE Tablet can be mounted either in the traditional way using the included camera and tripod support rails, hood and beam splitter glass, or under the lens for use with retro-reflective light. Suitable for most cameras. W/O remote control for text scroll speed , next chapter etc. Datavideo iPrompter software is available as free download App store REMOTE CONTROL NOT INCLUDED Choose a Wired, wireless or Bluetooth option	102 240 Ft
Datavideo	TP-500	TP-500 7"/ DSLR Prompter W/O Remote control 18 mm Rail Adjustable Mounting system included- ideal for DSLR Camera's Adjustable mount to hold Android & Apple tablets from 7" to 10" Tablet can also mounted under the lens for use with retro reflective light. REMOTE CONTROL NOT INCLUDED Choose a Wired, wireless or Bluetooth option	116 640 Ft
Datavideo	TP-650	TP-650 ENG Prompter in giftbox W/O remote control Larger frame Glass and mount. Suitable for ENG type cameras Adjustable mount to hold Android & Apple tablets from 7" to 10" Tablet can also mounted under the lens for use with retro reflective light. REMOTE CONTROL NOT INCLUDED Choose a Wired, wireless or Bluetooth option	142 560 Ft
Datavideo	WR-500	WR-500 universal Bluetooth Remote Control for Telerpompter. Bluetooth 4.0 can be used also in wired mode. Suitable for Apple devices , most Android tablets & Smartphones AVAILABLE MARCH 2016	38 880 Ft

Datavideo	HC-300	HC-300 Water/Dust resistant High Impact Case includes Precut Diced Foam- Also suitable for TP-300 Ext. 430x380x154mm Int. 395x320x117mm with pick&pluck foam for use with other equipment	25 632 Ft
Datavideo	HC-350	HC-350 Water/Dust resistant High Impact Case includes Precut Diced Foam Ext. 475x390x200mm Int. 442x350x175mm with pick&pluck foam for use with other equipment	47 520 Ft
Datavideo	HC-500	HC-500 Water/Dust resistant High Impact Case includes Precut Diced Foam- Also suitable for TP-500 with pick&pluck foam for use with other equipment	16 992 Ft
Datavideo	HC-600	HC-600 Water/Dust resistant High Impact Case includes Precut Diced Foam- Also suitable for TP-600 Ext. 515x415x200mm Int. 485x355x186mm with pick&pluck foam for use with other equipment	28 512 Ft
Datavideo	HC-650	HC-650 Water/Dust resistant High Impact Case includes Precut Diced Foam Ext. 530x355x225mm Int. 510x292x178mm with pick&pluck foam for use with other equipment	47 520 Ft
Datavideo	HC-700	HC-700 Water/Dust resistant High Impact Case includes Precut Diced Foam Ext. 560x355x290mm Int. 510x290x240mm with pick&pluck foam for use with other equipment	59 040 Ft
Datavideo	HC-800	HC-800 water/dust resistant High impact case. includes precut diced foam. case used in PLK400 lightingkit. ext: 625x420x340mm int: 581x360x298 mm	64 800 Ft
Datavideo	LBK-2	Look back kit for tripod mount. Ideal for monitors to be mounted directly under a camera. (VESA mount for 24"-32" monitors) To be used in conjunction with virtual studio or other live applications.	19 872 Ft
Datavideo	TP-300GLS	Glass replacement for TP-200/300	28 512 Ft
Datavideo	TP-500GLS	Glass replacement for TP-500	22 752 Ft

Glass replacement for TP-600

TP-600GLS

36 000 Ft

Camera Cloth replacment for TP-200 /300

Datavideo

CC-100

9 216 Ft

Intercom Systems

Intercom/ talkback system (max. 8 ch). Includes base station, gooseneck mic. and light for base station, 4x ITC100 SL Belt Pack (see ITC-100 SL for more details)

Datavideo

ITC-100

283 680 Ft

Intercom/talkback system as 2205-2000 but including 4 pcs. HP-1E headsets

Datavideo

ITC-100HP1-4

367 200 Ft

Additional Belt pack kit for ITC-100. Contains: 1x ITC-100SL Beltpack, 1x TD-3 tally light, 1x CB-7 1.2 M tally cable, 1x MC-1 Microphone headset, 1x CB-3 20 meter Intercom cable 1x CB-17

Datavideo

ITC-100SL

50 400 Ft

Standard One Ear Headphone with mic. for ITC-100SL.

Datavideo

MC-1

3 168 Ft

Heavy Duty Professional One Ear Headphone with microphone. HP-1E does have one 3,5 mm jack for Mic & Ear to fit into beltpack or ITC-100 base station

Datavideo

HP-1E

22 752 Ft

Heavy Duty Professional Two Ear Headphone with microphone. HP-2A does have one 3,5 mm jack for Mic & Ear to fit into beltpack or ITC-100 base station

Datavideo

HP-2A

30 240 Ft

3,5 mm jack to Headphone / Mic adapter. To use a standard (non usb) Skype headset with microphone with ITC-100 SL Beltpack

Datavideo

CB-17

1 152 Ft

SE-2800 Intercom/ Tally cable (Also for SE-2200)

Datavideo

CB-28

4 896 Ft

SE-3000 Intercom/ Tally cable		
Datavideo	CB-29	10 368 Ft
Tally cable (male to Female) for SE500/600/900 15 pin		
Datavideo	CB-42	2 016 Ft
SE-700/1200 Intercom/ Tally cable		
Datavideo	CB-59	3 456 Ft
XLR Gooseneck light for ITC-100.		
Datavideo	LP-1	16 992 Ft
XLR Gooseneck microphone for ITC-100.		
Datavideo	MC-2	19 872 Ft
Tally Box TB-20. Passive junction box for easy connection of tally output of Panasonic Switchers (1x 25 Pin Sub D) to Datavideo ITC-100 / ITC-200 tally interface (2x 15 Pin Sub-D) 2x 15-15 pin cable for connection between TB-20 and ITC-100 / ITC-200 included		
	TB-20	33 120 Ft
Tally Light Bi color (Red/Green) Only in combination with ITC-100 Package contains; 4x TD-3; 4x CB-7 (GPI Cable); 4x Mounting straps Set of 4		
Datavideo	TD-3	22 752 Ft
Character Generators		
IEEE1394/ VGA to SDI / DV Scan Conversion software Ideal solution for PowerPoint & similar using DV Mixer such as SE-800		
Datavideo	PPT-100	50 400 Ft
CG-250HD HD-SD Character generator software.		
Datavideo	CG-250	128 160 Ft
HD/SD Character Generator Kit - Title Creator 200 Interface with CG-200 software HD CG system for mobile broadcasting, live conferences and dynamic video presentations. Works on standard Windows laptop or pc with HDMI interface. Supports vision mixers with and without DSK. No additional PCI -SDI adapter card required. Supports DSK function via HDMI or SDI overlay with optional TC-200. Supports HD video with 1080i 50/ 59,94/ 60 and 720P50 /59.94/ 60 and SD Video 576i/ 480i s Supports all Windows fonts. Compatible with Windows 7/ 8 (including CG-200 SOFTWARE)		
Datavideo	TC&CG-200	185 760 Ft

	CG-350	HD & SD SDI Character Generator Software for live text using HD-SD SDI overlay input facility. The CG-350 is Windows-based character generators designed for live production and post production. Also suitable for Arabic text. Text direction can be changed. Will work with BMD Decklink or AJA Xena card, as a downstream keyer or as key and fill sources (depending on the card). Dynamic lower thirds 32 Bit color and animated text layers. WINDOWS ONLY Auto-updating text fields, live time clock and program-independent banner crawls (CG-350 only) Softwarekey by Dongle.	450 720 Ft
Datavideo	CG-500	CG-500 SD/HD Advanced TimeLine based CG for live / post production Real time graphic render, supports flexible play control of multiple playlists, realtime multi-layer play at the same time. WINDOWS ONLY compatible with Decklink Extreme 3D + card This is a broadcast-standard titling programme, with high class templates,IPTV to AV presentations external data support and GPU-rendered effects. It's suitable for everything from webstreaming and Live TV.	709 920 Ft
Character Generators ('Turn-key')			
Datavideo	CG-350 STUDIO	CG-350 HD/SD Live CG Turnkey system, fully configured in Desktop PC and ready to go. Datavideo CG-350 software preloaded INCLUDING DONGLE (item 2400-1050) HP hardware, 1Year Warranty. Fitted with Blackmagic Decklink Extreme 4K Optional available HP Monitor LE-2202 see (code 2800-0500)	1 368 000 Ft
Datavideo	CG-350 STUDIO (2U)	CG-350 HD/SD Live CG Turnkey system, fully configured in 2U rackmount PC and ready to go. Datavideo CG-350 software preloaded INCLUDING DONGLE (item 2400-1050) HP hardware, 1Year Warranty. Fitted with Blackmagic Decklink Extreme 4K Optional available HP Monitor LE-2202 see (code 2800-0500)	1 540 800 Ft
Datavideo	CG-500 STUDIO	CG-500 HD/SD Live CG Turnkey system, fully configured and ready to go. Datavideo CG-500 software preloaded INCLUDING DONGLE (item 2400-1060) HP hardware, 1Year Warranty. Fitted with Blackmagic Decklink Extreme 4K Optional available HP Monitor LE-2202 see (code 2800-0500)HP Computers are shipped under full HP 3-3-3 International warranty. Blackmagic covered by BMD	2 145 600 Ft
Virtual Studio (Trackless)/Keying			
Datavideo	TVS-1000A	Trackless Virtual Studio System, Turn-key solution with: Easy to use Multi-language user interface with up to 3 screens preview/multiviewer/UI Built in Character Generator, 2 Downstream keyers, 2 Clip players, still store and audio mixing Internal recorder highly-efficient H.264 and MPEG 2 recording format 1x HDMI input / output (no Tally control) with Aux input Supports direct streaming to Adobe Flash encoder, Ustream and Livestream PC including Software and remote control RMC220.	1 771 200 Ft
Datavideo	TVS-1200A	Trackless Virtual Studio System, Turn-key solution with: Easy to use Multi-language user interface with up to 3 screens preview/multiviewer/UI Built in Character Generator, 2 Downstream keyers, 2 Clip players, still store and audio mixing Internal recorder highly-efficient H.264 and MPEG 2 recording format Dual channel trackless virtual studio with HD-SDI in-and outputs An Aux input is available for powerpoint or video signals. Supports direct streaming to Adobe Flash encoder, Ustream and Livestream PC including Software and remote control RMC220	2 404 800 Ft
Datavideo	TVS-2000A	3D Camera tracking virtual studio set with HD-SDI I/O Turn Key solution including: RMC-280 controller for switching, phase and camera control Aux board for presentations or other external footage Optional: PTC-150 Pan & Tilt camera with tracking feedback and bracket for talent preview	3 254 400 Ft
Datavideo	MAT-2	Green Color mat for Chroma Keying 1.8 meter * 27 meter	217 440 Ft
Datavideo	MAT-2M	Green Color mat for Chroma Keying 1.8 meter wide and XX meter long. This item can be ordered per meter.	8 352 Ft

Green Color Tape 48mm * 25 Mtr.

	TA-1		5 472 Ft
Datavideo	PLK-400	PLK-400 Chromakey Lightkit. comprising 3X 308 LED Daylight with softbox for Background and 1x 160 LED Bicolor light with Softbox for talent . 4 x Mains powersupply, 4x Lighting stands. Supplied in wheeled hardcase with custom cut foam. Lights can run off Sony NP-F type and supplied with hotshoe adapters. Filters, diffuser, blue, magenta. Adapters for Panasonic battery (CGR-D series) Battery box for 6 AA batteries.	335 520 Ft

Datavideo	PLK-300	PLK-300 Portable light kit. Comprising of 3X 308 LED Bi Colour Lights. 3 X Light stands. Can be powered by Sony NP-F, Panasonic CG-D or AA Batteries. Batteries and main PSU are not included. Supplied in Wheeled hard case with custom cut foam.	257 760 Ft
------------------	----------------	--	------------

Waveforms

Datavideo	VS-100	Waveform Vectorscope Monitor, Parade, Histogram, Video in thumbnails. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. Output resolution 1280*720. Rotary control though OSD interface.	214 560 Ft
------------------	---------------	--	------------

	VS-150	1RU Waveform Vectorscope Monitor, Parade, Histogram, Video in thumbnails. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. Output resolution 1280*720. Front panel control though OSD interface. (Optional rackmounts available RMK-1)	266 400 Ft
--	---------------	---	------------

Datavideo	VSM-100	2RU Waveform Vectorscope Monitor with 2 monitors (4,3") providing Parade, Histogram, Video. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. With front panel control. Viewing Angle Vert.40 Deg, Hor.60 Deg HDMI and SDI outputs (loop thru's)	563 040 Ft
------------------	----------------	--	------------

Datavideo	VSM-200	Dual Channel 2RU Waveform Vectorscope Monitor with 2 monitors (4,3") providing Parade, Histogram, Video. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. With front panel control. Viewing Angle Vert.40 Deg, Hor.60 Deg HDMI and SDI outputs (loop thru's)	830 880 Ft
------------------	----------------	---	------------

Audio mixers

	AD-200	1U Audio mixer, level adjustment and audio delaybox. The matrix type audio mapping function allows combinaiton of multiple audio input channels into one or more output channels. Up to 3 seconds audio delay is available to synchronize audio with video. 6 XLR audio channels input. Support 2 audio input modes, Mic and Line. 2 audio modes mono / stereo.	237 600 Ft
--	---------------	---	------------

Datavideo	AD-100M	Audio delay box with voice over functionality. Features Microphone input, RCA (phono) connector as well as XLR connectors. Max delay: 700 ms 1U size. 19" rackmount kit as option available.	122 400 Ft
------------------	----------------	--	------------

Datavideo	AM-100	19 inch rackmount audiomixer. 1U A 6 channel (4x mono+ 1x stereo input) audiomixer. Supports line and mic. level for Ch.1- Ch.4 48V Phantom power (on/ off) for Ch.1- Ch.4 Separate gain and level adjustment per channel	159 840 Ft
------------------	---------------	--	------------

Multiscreen processors

Datavideo	TWP-10	The TWP-10 4K Video Wall Processor 2x2 is a powerful, cost effective, and truly real time datavideo processor for multiple flat panel displays. Any setups for the display layout can be virtually possible with the control software. -4 HDMI outputs with resolution from 640x480 to 1920x1200 -Resolutions 640x480 to 4K2K@60 (YUV 4:4:4), interlaced or progressive -HDCP compliant -Settings Save/Recall function -Software control through USB and Ethernet -Resize, position, zoom for each HDMI output video	427 680 Ft
------------------	---------------	--	------------

LCD Monitors

Datavideo	TLM-170L	17,3" LED Backlight Desktop monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. 2x HDMI input. On Screen Time code display. Underscan- overscan. Safe Area indication. Blue only. Adjustable Color temperature. Supports embedded audio	257 760 Ft
Datavideo	TLM-170LR	17,3" LED Backlight 7U Rackmount monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. 2x HDMI input. On Screen Time code display. Underscan- overscan. Safe Area indication. Blue only. Adjustable Color temperature. Supports embedded audio.	283 680 Ft
Datavideo	TLM-170LM	17,3" LED Backlight 1U Foldable Racktray monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. 2x HDMI input. On Screen Time code display. Underscan- overscan. Safe Area indication. Blue only. Adjustable Color temperature. Supports embedded audio.	361 440 Ft
Datavideo	TLM-170P	17,3" LED Backlight Desktop monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. CVBS video input with loopthrough output. On Screen Time code display. Underscan- overscan. Safe Area indication. Adjustable Color temperature . Supports embedded audio.	516 960 Ft
Datavideo	TLM-170PM	17,3" LED Backlight 1U Foldable Racktray monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. CVBS video input with loopthrough output. On Screen Time code display. Underscan- overscan. Safe Area indication. Adjustable Color temperature . Supports embedded audio.	620 640 Ft
Datavideo	TLM-170PR	17,3" LED Backlight 7U Rackmount monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. CVBS video input with loopthrough output. On Screen Time code display. Underscan- overscan. Safe Area indication. Adjustable Color temperature . Supports embedded audio.	528 480 Ft
Datavideo	TLM-433	High Quality 3x 4,3", 16:9 ratio LCD/TFT monitor system. 4:3 ratio compatible. Panel resolution 480x270 pixels. View angle =(V)+40/-60, (H)+60/-60 degrees. Auto PAL/ NTSC detection. Individual adjustments for brightness, contrast, colour, tint (NTSC). 3x Composite video in (loop through). 2 Colour tally system. 19" Rackmountable, 2U High. Can be tilted +/- 30 degrees. 12V dc input. 110-240V ac adapter included.	257 760 Ft
Datavideo	TLM-434H	High Quality 4x 4,3", 16:9 ratio LCD/TFT monitor system. 4:3 ratio compatible. Screen Resolution: 480 x 272 pixels input: HD/SD SDI, HDMI. Output:HD/SD SDI loop through 12V dc input. 110-240V ac adapter included.	646 560 Ft
Datavideo	TLM-430	4.3" LCD Look Back Monitor, with enlarged BI Color Tally light. Two Cvbs video inputs: one for camera and one for return (live) feed from switcner Resolution 480x272 LCD, active matrix. CB-26 Breakout cable for lookback is optional available. 2200-9892 Supports both 16:9 & 4:3 aspect ratio. DC 6V power operation via AC adapter (incl.) or Sony BP-U / NP-F series battery (not incl.) Remote controllable by Datavideo RMC-200	76 320 Ft

		Kit of Look Back Monitor, Controller, Bracket & BH-08 Comprises: TLM-430 Look Back Monitor Bracket to mount Monitor & Datavideo DN-60(A) via Camera Hot Shoe RMC-200 Camera Remote Controller BH-08 Ball head CB-15U - 90 degree DV cable CB-26 Breakout cable	
Datavideo	TLM-43LB		108 000 Ft
Datavideo	TLM-102	Dual 10.1" 4RU Rack mount monitors designed for broadcast quality 1280*800 IPS Panel resolution Support 3G-SDI video and HDMI input with loop-through output Support column (YRGB peak), time code, waveform, vectorscope & audio level meter, peaking, zoom, pix to pix, underscan, check field, etc SDI, HDMI cross conversion Color temperature for user to select	309 600 Ft
Datavideo	TLM-700HD	High res. 7", 16:9 LCD/TFT monitor. 4:3 ratio compatible. Panel resolution: 800x480Pixels. HD/SD-SDI, (HD-)YUV, CV and HDMI input. Standard V-mount enabeling powering up with universal battery for in the field use. Audio indicator for SDI & HDMI . Safe area indicator	168 480 Ft
Datavideo	TLM-700HD-A	High res. 7", 16:9 ratio LCD/TFT monitor. Anton Bauer battery mount	168 480 Ft
Datavideo	TLM-700HD-C	High res. 7", 16:9 ratio LCD/TFT monitor. Canon BP-9xx battery mount	168 480 Ft
Datavideo	TLM-700HD-S1	High res. 7", 16:9 ratio LCD/TFT monitor Sony BP-Ux battery mount (like EX-1, EX-3)	168 480 Ft
Datavideo	TLM-700HD-S2	High res. 7", 16:9 LCD/TFT monitor Sony NP-Fxxx battery mount (like Z5)	168 480 Ft
Datavideo	TLM-700HD-P	High res. 7", 16:9 ratio LCD/TFT monitor. Panasonic CGA battery mount	168 480 Ft
Datavideo	TLM-702HD	2 x 7" 16:9 Wide Screen Monitors in 19" Rack Mount with 90 degree tilt Blue Only Function, Brightness, Contrast & Colour Adjustment (& Tint NTSC only). Colour Bars NTSC/PAL Auto Switching. Audio level Indicators . HD/SD-SDI, YUV, CV, HDMI & Tally Input. Headphone output. DC Input via 12v PSU (Supplied).	283 680 Ft
Datavideo	TLM-433JF	Universal Desktop Stand / Holder suitable for: SE-800 + TLM-404 & TLM-702 (or single monitor) with or without ITC-100 SE-1000 + 1 or 2 x TLM-433 with or without ITC-100	44 640 Ft

Datavideo	RMK-1	Rack Mount Kit for one or two 1U height products, such as VSM -150 Vector scope Half 19 inch rack mount unit: 2 x Rack Ear 1x Rack Panel (1U) 4x M4*8 screw Note: Not suitable for AD-100!	13 248 Ft
Datavideo	RMC-200	Remote control for TLM-430 lookback monitor, to switch between ACTUAL and CAMERA Monitor function. For use in combination with CB 23 -24 All-in One Cable Includes Control-L/ Lanc connector for simple start stop and zoom function. This function is not available on all Sony Camera's	30 240 Ft
Signal Converters			
Datavideo	DAC-7	Analog to SD-SDI video converter with CVBS/S-Video/YUV inputs. Also audio inputs are available for embedding purposes.	93 600 Ft
Datavideo	DAC-8P	HD/SD-SDI to HDMI converter & audio demux (1080P) Can be used for connecting the HD-SDI PGM out of a switcher to a projector with HDMI in.	79 200 Ft
Datavideo	DAC-9P	HDMI HD-Video to HD/SD-SDI Converter (1080P) also embeds audio from HDMI signal into HD-SDI signal. Supported input formats: 480i, 576i, 720P50/ 59,94/ 60, 1080i50/ 59,94/ 60 and 1080P50/ 59,94/ 60	79 200 Ft
Datavideo	DAC-50S	HD-SDI to SD analog video converter. Available outputs: YUV/S-Video(YC) / 2x CVBS (Supports PAL&NTSC)	93 600 Ft
Datavideo	DAC-60	HD/ SD-SDI to VGA converter. Supported HD input formats: 720P50/ 60, 1080i50/ 60 and 1080P24/ 25/ 30/ 50/60 Supported SD input formats: 525i (NTSC) and 625i (PAL) Supported VGA output formats (all at 60Hz): 800x600, 1024x768, 1280x800, 1280x1024, 1366x 768, 1400x1050, 1600x1200, 1920x1080, 1920x1200 (Firmware version V0.1.1.0 required)	93 600 Ft
Datavideo	DAC-70	Multi format up /down /cross converter "Many formats in (auto detect) to many formats out (by dipswitch selection)" Input connectors: VGA (up to 1600x1200), HDMI-video , (HD-)SDI and RCA audio. Output connectors: HDMI and 2x (HD) SDI. Video output formats: 480/576i, 720P50/59,94/60, 1080i50/ 59,94/60, 1080P23,98/24/25/50/60 The DAC-70 supports HDCP for HDMI input. Supports multi-channel audio (SDI / HDMI 8 ch audio embedded)	143 712 Ft
Datavideo	DAC-45	4K Up/Down/Cross converter designed to convert video signals from VGA, HDMI, SDI with Audio input to 4K HDMI or 3G-SDI output. It allows instant switching between 4K, HD and SD video formats. HDMI 2.0 input/output with 4:2:2 processing Supports 3G-SDI Level A/B, Reference input BB and Tri Level Sync Built in Super Resdolution Engine for 4K Up scaling and frame rate conversion	228 960 Ft
Datavideo	DAC-80	DAC-80 / 2 Channel Audio 1:1 transformer High quality ground loop isolator (with ground lift) to avoid audio hum XLR in / out	30 240 Ft

		3Gbps/HD/SD-SDI Audio de-embedder, 4 Analog mini XLR audio outputs. Each set of channels can be selected with the dipswitches (selection of group 1-4) Incl. 2 mini XLR 'pigtaills'	
Datavideo	DAC-90		79 200 Ft
Datavideo	DAC-91	3Gbps/HD/SD Analogue audio embedder, embedding 2 channels of analog audio into SDI video signal. Automatically detects 3G,HD SDI signal. 2 analog inputs (Mini XLR or RCA x2) Audio level indicator display. Audio level adjustment and control via DIP switches. Including 2 mini XLR 'pigtaills'	90 720 Ft
Datavideo	RMK-2	19" 2 U rack mount holder for up to 8 x DAC Converters. Mounts up to 8 datavideo converters in a single 2U rackframe. Single power Connection Suitable for DAC-8(p), DAC-9(p) DAC-60 , DAC-70	79 200 Ft
Datavideo	MB-4-S1	DAC-series mountingbracket with Batteryholder for power support. This mounting braketr can easily connect to Tripod or other. Battery holder can support widely useed batteries and makes your DAC portable. Battery mount for SONY BP-U60, BP-U30 Compatible with Datavideo DAC series, DAC60/70, DAC8P/9P, VP-597	19 872 Ft
Datavideo	MB-4-S2	Battery mount for DAC converter compatible with SONY NP-F770/ 970/ 960/ 950	19 872 Ft
Datavideo	MB-4-P	Battery mount for DAC converter compatible with Panasonic CGA series	19 872 Ft
	MB-4-C	Battery mount for DAC converter compatible with CANON BP series	20 160 Ft
Datavideo	MB-4-S	Battery mount for DAC converter compatible with SONY NP-QM series	19 872 Ft
Datavideo	MB-4-BB	Battery mount for DAC converter compatible with/o battery plate	10 368 Ft
Datavideo	MB-5	DAC series Tripod mounting bracket for DAC series	6 912 Ft

		PD-2A Power Distributor providing 400 Watt rated power supply to cover most power requirements.	
	PD-2A		263 520 Ft
Datavideo	PD-4A	19 inch rackmount Redundant Power Center. PD-4A Center is specifically designed to provide a steady power supply for datavideo mobile studio applications. It provides a 300 watt rated power supply to cover most power requirements for a mobile studio, such as a video switcher, LCD monitors, video recorders, talk back system, and so on. It comes with a standard 19"/1U rack size design, the PD-4 makes system integration professional and reliable. With two AC power supplies, the PD-4 will still supply energy to your devices, even if one power source fails	424 800 Ft
		AC Power distributor For OB-VAN rack - special production only- NOCE	
Datavideo	PD-5		211 680 Ft
Datavideo	PD-6	PD-6 is a 19" rack mountable universal AC to DC power distribution center. Designed to supply steady and sequenced voltage for production kit whilst on location or in your studio. The PD-6 supplies a steady user chosen voltage 12,14,4,24, or 48 volts. Related products for 48V are : DC/DC converter DDC-4012H code 2600-3011 CB-22 H cable 30 mtr. Code 2200-9882 CB-23 H Cable 50 mtr. Code 2200-9883	396 000 Ft
Datavideo	DDC-4012H	DC/DC converter for use in combination with PD-6 power distribution centre and CB-22H/ 23H All in One cable related products for 48V are : PD-6 PowerCenter CB-22 H cable 30 mtr. Code 2200-9882 CB-23 H Cable 50 mtr. Code 2200-9883	47 520 Ft
Datavideo	DDC-2512	DC/DC converter for Phantom power in combination with PD-3 power distribution centre and CB-22/ 23 All in One cable Fixed 12V DC output (max 2.5A)	33 120 Ft
Rack Panels			
		19 inch, 3 Rackunit cover panel Can be used with MS-Series or OBV-Series products	
Datavideo	RP-11		13 248 Ft
		19 inch, 1 Rackunit cover panel Can be used with MS-Series or OBV-Series products	
Datavideo	RP-12		6 912 Ft
		Hinged Rack Tray to hold SE-900 Keyboard Requires 3 RU Can be used with MS-Series or OBV-Series products	
Datavideo	RP-28		59 040 Ft
		19 inch patch panel for ITC-100. 8x 5 pin XLR I/O connector for ITC-100SL Can be used with MS-Series or OBV-Series products	
Datavideo	RP-31		53 280 Ft

MS-900 cable set		
Datavideo	RP-34	38 880 Ft
Datavideo	RP-45	19" Composite video distribution amplifier (1 to 8) PSU included Can be used with MS-Series or OBV-Series products
Datavideo	RP-50	19 inch, 1 Rackunit blind panel with a Euro powerconnector on the outside providing power inside a rack with a regular power socket (UK, US and Euro compatible) Can be used with MS-Series or OBV-Series products
Datavideo	RP-51	19 inch, 1 Rackunit built up of 2 half 19" components; *Left side VP-445 HD/SD distribution amplifier with connections *Right side the AD-100 with interface facing outside Can be used with MS-Series or OBV-Series products
Datavideo	RP-61	RP-61 RP-ONE U (blank panel) universal Neutrik connector panel.
Datavideo	RP-64	VIDEO BUFFER and HD-SDI to analog converter rear panel
Datavideo	RP-BRIDGE	RP-BRIDGE rear panel for SDI input
	PP-ONE X	Rear panel for SDI output + power out
Datavideo	PP-ONE D	Rearpanel for SDI connector
Datavideo	PP-BASE	Base plate OBV 2800

Base plate for Rack fit Mercedes Viano

Datavideo **OBV base V** 237 600 Ft

3U cover plate for OBV

Datavideo **PP-3U-cover** 4 032 Ft

Cover plate for Cabling OBV

Datavideo **PP-Cover** 22 752 Ft

HDMI Peripherals

Rear panel for 3 pin XLR +HDMI connector

Datavideo **PP-ONE E** 73 440 Ft

Rearpanel for HDMI connector and power in

Datavideo **PP-ONE Z** 105 120 Ft

19 inch, 1 Rackunit with 2 XLR connectors and 3 HDMI connectors
Can be used with MS-Series or OBV-Series products

RP-52 99 360 Ft

HD/SD HDMI Distribution with ITC-100 breakout panel

Datavideo **RP-62** 162 720 Ft

DVI <-> HDMI Cable black 1.8 mtr.

Datavideo **CB-20** 5 184 Ft

HDMI Active Optical Cable with High performance. 30 meter. Can transmit 4K@60Hz UHD up to more than 100 mtr. Support HDMI 2.0, Support HDCP 2.2. Plug and Play. Highly resistant with EMI and RFI. No external power needed.

Datavideo **CB-60** 96 480 Ft

HDMI Active Optical Cable with High performance. 50 meter. Can transmit 4K@60Hz UHD up to more than 100 mtr. Support HDMI 2.0, Support HDCP 2.2. Plug and Play. Highly resistant with EMI and RFI. No external power needed.

Datavideo **CB-61** 122 400 Ft

		HDMI Active Optical Cable with High performance. 100 meter. Can transmit 4K@60Hz UHD up to more than 100 mtr. Support HDMI 2.0, Support HDCP 2.2. Plug and Play. Highly resistant with EMI and RFI. No external power needed.	
Datavideo	CB-62		93 600 Ft

Cables

		IEEE1394 / DV Firewire Cable 1.8M (6P-4P) 400mbps	
--	--	---	--

Datavideo	DVM-2264		3 456 Ft
------------------	-----------------	--	----------

		IEEE1394 / DV Firewire Cable 1.8M (6P-6P) 400mbps	
--	--	---	--

Datavideo	DVM-2266		3 456 Ft
------------------	-----------------	--	----------

		High Quality 20M IEEE1394/DV Cable. 6 Pin- 6 Pin (6P-4P Adapt available) 200mbps. Suitable for all DV / DVCAM.	
--	--	--	--

Datavideo	DVM-2066		22 752 Ft
------------------	-----------------	--	-----------

		To convert S-video connector with lock to 2 BNC connectors Usefull in combination with SE-500. Can transmit S-video over long distance by using two standard BNC cables. SET of 2 pcs.	
--	--	--	--

Datavideo	CB-2		3 744 Ft
------------------	-------------	--	----------

		20m Intercom extension Cable 5 pin XLR connector for use in combination with ITC-100SL. Max. 200 mtr.	
--	--	---	--

Datavideo	CB-3		13 248 Ft
------------------	-------------	--	-----------

		50m Intercom extension Cable 5 pin XLR connector for use in combination with ITC-100SL max. 200 mtr.	
--	--	--	--

Datavideo	CB-4		30 240 Ft
------------------	-------------	--	-----------

		GPI / Tally cable 1.2 Mtr.	
--	--	----------------------------	--

Datavideo	CB-7		864 Ft
------------------	-------------	--	--------

		3,5 mm(male) jack to 4 pin XLR (female) cable adapter for ITC-100 SL beltack	
--	--	---	--

Datavideo	CB-8		2 304 Ft
------------------	-------------	--	----------

		DV-I Cable black 1.8 mtr. For use with SE-1000	
--	--	--	--

Datavideo	CB-9		6 336 Ft
------------------	-------------	--	----------

High Quality HD/ SD cable,YUV 4*BNC- 4*BNC, length 3Mtr. Made by Canare (Japan)

Datavideo	CB-10		22 752 Ft
High Quality SD cable,YUV 4*BNC-4*BNC, lenght 3Mtr. Made by Canare (Japan)			
Datavideo	CB-14		8 064 Ft
DV cable with 6 pin FireWire connector in 90 degrees upright position. Very usefull cable for use with all HDD recorders as it will reduce the downforce on the connector lenght about 20 cm			
Datavideo	CB-15U		4 032 Ft
DV cable with 6 pin FireWire connector in 90 degrees down right position. Very usefull tool for use with all HDD recorders as it will reduce the downforce on the connector lenght about 20 cm			
Datavideo	CB-15D		4 032 Ft
DVI-D <-> DVI-D Cable black 1.8 mtr.			
Datavideo	CB-19		6 048 Ft
All-in One features: 1x 4 pin XLR power cable, 1x5 pin XLR Intercom, 1x BNC for Video, 1x BNC for return Length: 30 meter Related products for 48V are : PD-6 PowerCenter (2205-1060) DC/DC converter DDC-4012H (2600-3011) VP-605H heavy duty cable extender (2332-2010)			
Datavideo	CB-22H		70 560 Ft
All-in One features: 1x 4 pin XLR power cable, 1x5 pin XLR Intercom, 1x BNC for Video, 1x BNC for return Length: 50 meter Related products for 48V are : PD-6 PowerCenter (2205-1060) DC/DC converter DDC-4012H (2600-3011) VP-605H heavy duty cable extender (2332-2010)			
Datavideo	CB-23H		105 120 Ft
All in one cable for use with SD-SDI and Cvbs MVS systems. 18 AWG Includes connectors for Intercom & Tally, Video SD-SDI & return video for Look Back monitor Length: 100 meter			
Datavideo	CB-24		168 480 Ft
RS-232 control cable for recorder DN-60			
Datavideo	CB-25		1 152 Ft
All-in One Cable 30 meter: 1x HD/ SD SDI, 1x Cvbs for retun video 2x RJ45 connector for use icw MCU-100 and AD-1 and 5 Pin XLR for Talk back and Tally			
Datavideo	CB-30		79 200 Ft

		All-in One Cable 50 meter: 1x HD/ SD SDI, 1x Cvsb for retun video 2x RJ45 connector for use icw MCU-100 and AD-1 and 5 Pin XLR for Talk back and Tally	
Datavideo	CB-31		116 640 Ft
		Mini DIN 9 to 4* BNC	
Datavideo	CB-40		5 472 Ft
		Dual side audio 3-pin XLR cable	
Datavideo	CB-41		5 472 Ft
		D-SUB 15 pin Tally cable (male to Female) for SE500/600/900	
Datavideo	CB-42		2 016 Ft
		All in one cable for CCU-100 art. nr. 2205-1200 Length: 30 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	
Datavideo	CB-43		128 160 Ft
		All in one cable for CCU-100 art. nr. 2205-1200 , Length: 50 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	
Datavideo	CB-44		191 520 Ft
		All in one cable for CCU-100 art. nr. 2205-1200, Length: 80 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	
Datavideo	CB-45		266 400 Ft
		All-in One Cable L:30 Mtr. HD-SDI For HS series switcher. The cable includes SDI, intercom and Tally cable.	
Datavideo	CB-46		53 280 Ft
		All-in One Cable L:50 Mtr. HD-SDI. For HS series switcher. The cable includes SDI, intercom and Tally cable.	
Datavideo	CB-47		82 080 Ft
		All in one cable for CCU-100 art. nr. 2205-1200, Length: 100 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	
Datavideo	CB-49		398 880 Ft

CR-1 including 100 meter CCU cable CB-49

Datavideo	CR-49		432 000 Ft
-----------	-------	--	------------

Cable Reel w/o cable

Datavideo	CR-1		70 560 Ft
-----------	------	--	-----------

30cm 6P(female)-4P(male) adapter - to convert 6P fitting to 4P fitting.

Datavideo	CA-64		4 032 Ft
-----------	-------	--	----------

Time Base Corrector

Datavideo	TBC-5000	TBC & Matrix switcher Frame synchronizer 4:2:2 Multi functions with 4 TBC. 4 in -1 out synchronization video switcher, 4 in -4 out a synchronous 4 in 2 out . Combined with DVK-100 chromakeyer, user can assemble low cost dual camera virtual broadcast studio for entertainment applications. Can be mounted in 19 inch rack see bracket 2200-9530	214 560 Ft
-----------	----------	---	------------
