

Switchers / Vision mixers

	Termékkód	Leírás	Listaár
Datavideo	SE-500	4 Input Analogue Video Switcher (Unibody) with Digital Signal Processing. S-video (Y/C) and Composite video (CVBS) Inputs (auto detect) Selectable YUV / S-video (Y/C) or Composite Outputs 2x Microphone inputs, Quad view display, Preview, & Tally Output, RS-232/Midi	256 500 Ft
Datavideo	SE-600	8 Input Standard Definition Switcher (Unibody) with: 6 Composite (CVBS) & 1x DVI-D & 1x DVI-I Inputs 3x CVBS Program, 2x CVBS Aux Output 2x DVI-D for Multi-Viewer with clock and audio level indicator 2x PIP, Luma key, Dual logo store, Mix/Wipe, Audio leveling RS-232 & GPI control interface	513 000 Ft
Datavideo	SE-700	4 Input Digital Video Switcher (Unibody), easy to learn and use. SE-700 includes 2 HD-SDI and 2 HDMI Inputs It features 2 assignable HD-SDI and 1 HDMI Output 2 XLR Inputs for audio embedding Built-in multiviewer, Supporting Linear/Luma Key, Wipe, Mix & Cut Transitions, 1 DSK, Full M/E Preview function, Frame store, Dedicated Stills Buffer for 24 Images XPT (Cross Point Assignment), PC & Tablet control also available Tally output, GPI Output	461 700 Ft
Datavideo	SE-1200MU	6 Input HD Digital Video Switcher (1RU mainunit, GUI as UI) with: 4x HD-SDI and 2x HDMI Inputs each input Synchronised 2x HD-SDI & 2x HDMI Outputs (Can be assigned as PVW/PGM/Clean/MV) 2 Upstream Keyers, supporting Chroma Key & Linear/Luma Key 2 DSK's, 1 PIP, Wipe, Mix & Cut Transitions, Full M/E Preview function, Up to 24 images Still-store, Xpoint assignment, PC/Tablet control, built-in Multiviewer (streaming) & Tally/GPI, 2 XLR Inputs for audio embedding	384 750 Ft
Datavideo	RMC-260	Hardware control panel for SE-1200MU videoswitcher (Serial control) AVAILABLE MARCH 2016	128 250 Ft
Datavideo	SE-2200	6 Input HD/SD Digital Video Switcher (Splitunit) with: 6x HD-SDI or 4x HD-SDI +2x HDMI Inputs (Synchronised) 6x HD-SDI (XPT/AUX/PVW/PGM), 2x HDMI (Multiviewer only) FTB, Mix, Cut, Wipe effects, 2x PIP & a DSK INCLUDING: Title Creator Software (CG-200) For more info see p.n. 2400-1030 Switcher operation mode HD (1080i / 720P) or SD (576i) switcher	769 500 Ft
Datavideo	SE-2200 MU	SE-2200MU: 6 input switcher 19" main unit	641 250 Ft
Datavideo	SE-2200 KB	SE-2200KB: control panel for SE-2200 main unit	141 075 Ft
Datavideo	SE-2800-8	8 Input Digital Video Switcher (Splitunit) with: 8 HD-SDI Inputs of which 2 selectable to HDMI Inputs 3 SDI Outputs assignable (AUX/PGM/PVW/clean-PGM) 2 HDMI Outputs for Multiview monitoring (2nd output can be PVW/PGM as well) 2 DSK's supporting Key and Fill, Cut/Mix/Wipe with borders, Clock & Countdown counter on multiscreen, 2 PIP displays with user-defined borders Tally, GPI interface and RJ45 for firmware upgrade Audio Delay up to 16 fields, or 8 frames	1 282 500 Ft
Datavideo	SE-2800-12	12 Input Digital Video Switcher (Splitunit) with: 12 HD-SDI Inputs of which 3 selectable to HDMI Inputs 3 SDI Outputs assignable (AUX/PGM/PVW/clean-PGM) 2 HDMI Outputs for Multiview monitoring (2nd output can be PVW/PGM as well) 2 DSK's supporting Key and Fill, Cut/Mix/Wipe with borders, Clock & Countdown counter on multiscreen, 2 PIP displays with user-defined borders Tally, GPI interface and RJ45 for firmware upgrade Audio Delay up to 16 fields, or 8 frames	1 474 875 Ft
Datavideo	SE-2800-8 main	SE-2800 HD-SDI Digital Video switcher, 8 input Main unit only	1 077 300 Ft
Datavideo	SE-2800-12 main	SE-2800 HD-SDI Digital Video switcher, 12 input Main unit only	1 256 850 Ft
Datavideo	SE-2800-Keyboard	SE-2800 Control panel to control SE-2800 Main unit	243 675 Ft
Datavideo	SE-2800-4 Inp	SE-2800 optional input board (4CH) for SE-2800-8 and HS-2800	192 375 Ft
Datavideo	600DVO	Optional DV- SDI OUTPUT board for SE-600 / HS-600. 2 DV and 2 SDI outputs at the same time. With embedded audio on SDI/ DV out. (backplate height appr. 28 mm) Suitable for SE-600 from sn 00364911 and up)	89 775 Ft
	RKM-2000	Solid aluminium 19" rack mount holder. Size 2U to hold 1U recorder and 1U Talkback system. Universal use for SE-2000, SE-600 and more.	75 668 Ft
	TB-5	Tally controlbox for use i.c.w. SE-500 or RMC-90 or SE-2000 (special cable needed) Contains also; 4 x TD-2 tally light, 4x CB-7, 1.2 m Tally cable, 1x 15 pin SUB-D male-female	38 475 Ft
Mobile Systems (Case)			
Datavideo	HS-600	Handcarry System, Portable production unit, designed as a suitcase providing; Standard definition vision mixer with 2 PIP, Luma key & built in Multiviewer with clock and audio level indicator (als available external through DVI-D) Video inputs: 6 CVBS, 1 DVI-D, 1 DVI-I Video outputs: 2x CVBS Aux & 2x CVBS Built-in Intercom system and 17.3" integrated monitor. (Main power or 12V)	1 333 800 Ft

Datavideo	HS-1200	<p>Handcarry System, Portable production unit, designed as a suitcase providing; HD/SD Digital video switcher with XPT assignments, FTB, Mix, Cut, Wipe effects, PiP & 2x downstream keyer Video inputs: 6x HD-SDI or 4x HD-SDI +2x HDMI Video outputs: 1x HD-SDI & 1x HDMI (XPT/AUX/PVW/PGM) Tally/GPI output. Built-in 17.3" (1600x900) integrated monitor. (Main power or 12V) AVAILABLE MARCH 2016</p>	768 218 Ft
Datavideo	HS-2200	<p>Handcarry System, Portable production unit, designed as a suitcase providing; HD/SD Digital video switcher with XPT assignments, FTB, Mix, Cut, Wipe effects, 2x PiP & a downstream keyer Video inputs: 6x HD-SDI or 4x HD-SDI +2x HDMI Video outputs: 5x HD-SDI (XPT/AUX/PVW/PGM), 1x HDMI (Multiviewer only) Built in TC-200 title creator technology and FREE CG-200 software. For more info see art. 2400-1030 Built-in Intercom system and 17.3" integrated monitor. (Main power or 12V) Switcher operation mode HD (1080i / 720P) or SD (576i) switcher</p>	1 410 750 Ft
Datavideo	HS-2800	<p>Handcarry System, Portable production unit, designed as a suitcase providing; HD/SD Digital video switcher with dual logo inserter/store, FTB, Mix, Cut, Wipe effects, 2x PiP & 2 downstream keyers & audio follow video mode Video inputs: 8x HD-SDI of which 2 are switchable to HDMI (Expandable to 12 inputs) Video outputs: 2x HD-SDI Built-in Intercom system and 17.3" integrated monitor. (Main power or 12V) Switcher operation mode HD (1080i / 720P) or SD (576i) switcher</p>	1 923 750 Ft
Mobile Systems (MS-Series)			
Datavideo	MS-2800A	<p>Mobile Production System, fitted in an 8U flightcase providing a turn-key solution with: -HD/SD Digital video switcher with dual logo inserter/store, FTB, Mix, Cut, Wipe effects 2x PiP & 2 downstream keyers & audio follow video mode Video inputs: 8x HD-SDI of which 2 are switchable to HDMI (Expandable to 12 inputs) Video outputs: 2x HD-SDI Switcher operation mode; HD (1080i / 720P) or SD (576i) switcher -TFT LCD Monitor 1U Foldable Racktray, 17,3" (1600x900) [TLM-170GM] -Intercom system 8 ch. base station, gooseneck mic. , light for base station, 4x ITC100 SL Belt Pack [ITC-100] -HD/ SD Harddrive recorder with removable 2.5" HDD (SSD/ HDD not included) [HDR-70] -Audio delay box with voice over functionality [AD-100M] -400 Watt Power Distributor [PD-2A]</p>	3 942 405 Ft
Datavideo	MS-2800B	<p>Mobile Production System, fitted in an 8U flightcase providing a turn-key solution with: -HD/SD Digital video switcher with dual logo inserter/store, FTB, Mix, Cut, Wipe effects, 2x PiP & 2 downstream keyers & audio follow video mode Video inputs: 8x HD-SDI of which 2 are switchable to HDMI (Expandable to 12 inputs) Video outputs: 2x HD-SDI Switcher operation mode; HD (1080i / 720P) or SD (576i) switcher -TFT LCD Monitor 1U Foldable Racktray, 17,3" (1600x900) [TLM-170GM] -Intercom system 8 ch. base station, gooseneck mic. , light for base station, 4x ITC100 SL Belt Pack [ITC-100] -HD/ SD Harddrive recorder with removable 2.5" HDD (SSD/ HDD not included) [HDR-70] -Audio delay box with voice over functionality [AD-100M] -HD/SD-SDI Waveform Vectorscope Monitor, Parade, Histogram [VSM-100] -400 Watt Power Distributor [PD-2A] -PD-6 PSU to power ext. devices (voltages: 12,14,4,18, or 48)</p>	4 917 105 Ft
Datavideo	MS-2800C	<p>Mobile Production System, fitted in an 8U flightcase providing a turn-key solution with: -HD/SD Digital video switcher with dual logo inserter/store, FTB, Mix, Cut, Wipe effects, 2x PiP & 2 downstream keyers & audio follow video mode Video inputs: 8x HD-SDI of which 2 are switchable to HDMI (Expandable to 12 inputs) Video outputs: 2x HD-SDI Switcher operation mode; HD (1080i / 720P) or SD (576i) switcher -TFT LCD Monitor 1U Foldable Racktray, 17,3" (1600x900) [TLM-170GM] -Intercom system 8 ch. base station, gooseneck mic. , light for base station, 4x ITC100 SL Belt Pack [ITC-100] -HD/ SD Harddrive recorder with removable 2.5" HDD (SSD/ HDD not included) [HDR-70] -Mono/Stereo audio mixer 6 channel with delay function (up to 3sec) [AD-200] -400 Watt Power Distributor [PD-2A]</p>	4 027 050 Ft

	MS-2800D	<p>Mobile Production System, fitted in an 8U flightcase providing a turn-key solution with:</p> <ul style="list-style-type: none"> -HD/SD Digital video switcher with dual logo inserter/store, FTB, Mix, Cut, Wipe effects, 2x PiP & 2 downstream keyers & audio follow video mode Video inputs: 8x HD-SDI of which 2 are switchable to HDMI (Expandable to 12 inputs) Video outputs: 2x HD-SDI Switcher operation mode; HD (1080i / 720P) or SD (576i) switcher -TFT LCD Monitor 1U Foldable Racktray, 17,3" (1600x900) [TLM-170GM] -Intercom system 8 ch. base station, gooseneck mic. , light for base station, 4x ITC100 SL Belt Pack [ITC-100] -HD/ SD Harddrive recorder with removable 2.5" HDD (SSD/ HDD not included) [HDR-70] -Mono/Stereo audio mixer 6 channel with delay function (up to 3sec) [AD-200] -HD/SD-SDI Waveform Vectorscope Monitor, Parade, Histogram [VSM-100] -400 Watt Power Distributor [PD-2A] -PD-6 PSU to power ext. devices (voltages: 12,14,4,18, or 48) -HD-SDI to SD analog video converter. Outputs: YUV/S-Video(YC) / 2x CVBS [DAC-50 s] -1 -> 4 HD/SD SDI Distribution Amplifier [VP-445] 	4 911 975 Ft
Mobile Systems (OBV-Series)			
	OBV-2800	<p>HD/SD 8 or 12 Channel Portable production unit (2-racks) including: 1 x SE-2800 8 Channel Digital Video Switcher; 2 x TLM-170HR: HD monitors for multiviewer/PGM; 1 x HDR-70: HD recorders for PGM and AUX; VSM-100: vectorscope / waveform monitor; ITC-100: 8-ch intercom / tally system with 8-Ch belt pack; AM-100: 5-ch audio mixer; AD-100: audio delay box; PD-2A: power distributor (8 x DC 12V); PD-6: 8-ch power center; RP-45: 8-ch CV return video; VP-445: 4-ch SDI amplifier; DAC-50 Digital/Analog converter. (CH 9-12 are optional)</p>	7 506 473 Ft
	OBV-2800-CCU	<p>HD/SD 8 or 12 Channel Portable Production Unit with Camera Control (2-racks) including: 1 x SE-2800 8 Channel Digital Video Switcher; 2 x TLM-170GR 3G-SDI TFT LCD Monitor; 1 x HDR-70 HD/SD Digital Video Recorder; 1 x VSM-100 Sampling Vector Scope Monitor; 1 x ITC-100 8 Way Intercom Talk Back System; 1 x MCU-200 Multi-Camera Control Unit; 1 x AD-200 Audio Level / Delay Control Panel; 1 x CCU-100P / CCU-100S / CCU-100I Camera control unit with complementary AD-2's; 1 x NVS-25 Video Streaming Server; 1 x RP-76 Rear Panel with LAN / HDMI. (CH 9-12 are optional)</p>	9 667 485 Ft
	OBV-RACK	19 inch.Rack for use with table which fit SE-900, SE-600, SE-2000, SE-3000 or blank table, Excl. table, mnt height rear 27U.	389 880 Ft
	OBV-T900/2800	19 inch foldable Table with cut-out for SE-2800 control panel Can be used with OBV-systems	164 160 Ft
	OBV-TB-3000/2000/600	Blank Table for OBV rack which hold SE-3000 control panel. (Also suitable for SE-2000/ SE-600) Depth appr. 48 cm.	169 290 Ft
	OBV Trolley	OBV Trolley to be used with OBV systems to move racks easily	64 125 Ft
	OBV-TB-BK	19 inch foldable Blank Table (Depth appr. 37,5 cm) Can be used with our OBV-systems	161 595 Ft
	OBV-JP	Joint plate to connect multiple OBV racks together (set of 3 plates)	8 978 Ft
4K Systems			
	KMU-100	<p>4K Dual channel multipurpose processing unit providing up/down/cross and scaling functionality</p> <p>Connectivity through HDMI 2.0, DisplayPort, 12G and 4x 3G</p> <p>This unit enables the user to get 4 dynamic "cut-outs" with zoom en motion features whereby each "cut-out" has it's own 3Gbps output (Virtual production with region of interest) Also for large public display purposes this unit can be used to "stitch" multiple displays to one large screen.</p> <p>For operational production purposes this unit can be operated by an optional Joystick</p>	1 282 500 Ft
PTZ Camera/Control			
	PTC-150 Black	<p>Full HD PTZ camera (Black) with:</p> <ul style="list-style-type: none"> 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's Built in Green/Red Tally LED Control thru IR/RF Controller/ RS-422/ DVIP Supports SONY VISCA Protocol Supports DVIP Control Protocol (F/W update to activate) With mounting bracket and Flip/Mirror function (& Day/Night function) 	640 994 Ft
	PTC-150 White	<p>Full HD PTZ camera (White) with:</p> <ul style="list-style-type: none"> 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's Built in Green/Red Tally LED Control thru IR/RF Controller/ RS-422/ DVIP Supports SONY VISCA Protocol Supports DVIP Control Protocol (F/W update to activate) With mounting bracket and Flip/Mirror function (& Day/Night function) 	640 994 Ft

Datavideo	PTC-150T	Full HD PTZ camera (Black) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's & HDBaseT Built in Green/Red Tally LED Control thru IR/RF Controller/ RS-422/ DVIP Supports SONY VISCA Protocol Supports DVIP Control Protocol (F/W update to activate) With mounting bracket and Flip/Mirror function (& Day/Night function)	897 750 Ft
Datavideo	PTC-150TW	Full HD PTZ camera (White) with: 1/2.8" High Definition 2.0 MegaPixels progressive MOS sensor 30x optical zoom (f=4.3 mm to 94.6 mm), Pan: 270deg/Tilt:+90deg, -20deg Dehazing technology allows the foggy or hazy images to be clear and sharp Digital Noise Reduction Function (DNR) Position coordinate report by real time per frame HD-SDI + CVBS + HDMI synchronously Output's & HDBaseT Built in Green/Red Tally LED Control thru IR/RF Controller/ RS-422/ DVIP Supports SONY VISCA Protocol Supports DVIP Control Protocol (F/W update to activate) With mounting bracket and Flip/Mirror function (& Day/Night function)	897 750 Ft
Datavideo	CB-55	CB-55 RJ-45 to RS232 converter	17 699 Ft
Datavideo	CB-57	CB-57 RS-232 to RJ 45 converter (connect from control panel to Cat 5 Only works with the PTC-120	17 699 Ft
Datavideo	HBT-10	HDBaseT Transmitter Box	127 994 Ft
Datavideo	HBT-11	HDBaseT Receiver Box	127 994 Ft
Datavideo	RMC-180	PTZ Camera Control Unit for up-to 4 Pan,Tilt & Zoom Cameras (PTC-150) Pan,Tilt & Zoom with speed control by large joystick Iris, Focus, Gain, and other functions over Ethernet 50 Presets/camera for position/zoom/focus and video calibration parameters Control thru standard CAT-5/6 cable upto 1000 meter Supports VISCA over RS-422 (point-to-point) Compatible with Datavideo's switcher tally indicators	243 675 Ft
Camera Control Unit			
Datavideo	MCU-100P	MCU 100 is a multiple camera controller for Panasonic Camcorders. Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported Panasonic camera's - AG-HPX255, AG-HPX300, AG-HPX301, AG-HPX302, AG-HPX304, AG-HPX370, AG-HPX371, AG-HPX372, AG-HPX500, AG-HPX502, AG-HPX600, AJ-PX800G, AJ-HDX900, AJ-HPX2700G, AJ-HPX3000	513 000 Ft
Datavideo	MCU-100S	MCU 100S is a multiple camera controller for Sony Camcorders. Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. 4 units Supported Sony Camera's : PMW EX3, PMW EX350, PMW 300K2, PMW 350K, PMW 320, PMW 400, PMW 510, PMW F5, PDW-F55, HDW-F900R	513 000 Ft
Datavideo	MCU-100J	MCU 100J is a multiple camera controller for JVC Camcorders. Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported JVC Camera's :GY-HM890U (LANC / PS/2), GY-HM850U (LANC / PS/2), GY-HM650U(LANC), GY-HM600U(LANC), GY-LS300CHU (LANC), GY-HM200U (LANC)	513 000 Ft
Datavideo	MCU-200P	MCU 200 is a multiple camera controller for Panasonic Camcorders.(Rackmountable, 1RU) Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported Panasonic camera's - AG-HPX500/502 HPX-600(NEW) AG-HPX300 / 301/ 302 / 304 / HPX 371	513 000 Ft
Datavideo	MCU-200S	MCU 200S is a multiple camera controller for Sony Camcorders.(Rackmountable, 1RU) Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. 4 units Supported Sony Camera's : EX-3, EX350, F55, F5	513 000 Ft
Datavideo	MCU-200J	MCU 200J is a multiple camera controller for JVC Camcorders.(Rackmountable, 1RU) Provides easy operation of major camera control functions. Extension up to 300M is possible by using Ethernet cable. Can provide detailed camcorder settingvalue by CV output via adapterbox. Included: Adapterbox AD-1 4 pcs. RJ-45 1.5M cable 1 pcs. , Power adaptor 1 pcs. Supported JVC Camera's : GY-HM890U /GY-HM850U/GY-HM650U/GY-HM600U/GY-HM200U/GY-LS300CHU	513 000 Ft

Datavideo	CCU-100P	Camera control unit for Panasonic camera's to connect and control 4 camera's, supports; HD/SD SDI video; Return video; viewfinder look back video; Two-way headset intercom; Record and Playback; Shutter speed and degree functions; Iris adjustment; AWB & ABB functions; White Balance A, B and Preset functions Knee & Bars functions; Gain adjustment; Tally, including; Power Supply; Ethernet Port for Remote Control; 4 x AD-2P Multi Transmission Adaptor Box; 4 x RMC-240 Remote Controller; 4x HP-3 headphones	1 277 370 Ft
Datavideo	CCU-100S	Camera control unit for Sony camera's to connect and control 4 camera's, supports; HD/SD SDI video; Return video; viewfinder look back video; Two-way headset intercom; Record and Playback; Shutter speed and degree functions; Iris adjustment; AWB & ABB functions; White Balance A, B and Preset functions Knee & Bars functions; Gain adjustment; Tally, including; Power Supply; Ethernet Port for Remote Control; 4 x AD-2P Multi Transmission Adaptor Box; 4 x RMC-240 Remote Controller; 4x HP-3 headphones	1 277 370 Ft
Datavideo	CCU-100J	Camera control unit for JVC camera's to connect and control 4 camera's, supports; HD/SD SDI video; Return video; viewfinder look back video; Two-way headset intercom; Record and Playback; Shutter speed and degree functions; Iris adjustment; AWB & ABB functions; White Balance A, B and Preset functions Knee & Bars functions; Gain adjustment; Tally, including; Power Supply; Ethernet Port for Remote Control; 4 x AD-2P Multi Transmission Adaptor Box; 4 x RMC-240 Remote Controller; 4x HP-3 headphones	1 277 370 Ft
Datavideo	AD-1P	AD-1P Camera adapter for use with MCU-100/200 -Panasonic (10 pin)	70 538 Ft
Datavideo	AD-1S	AD-1S Camera adapter for use with MCU-100S/200S -Sony (8 pin)	70 538 Ft
Datavideo	AD-1J	AD-1J Camera adapter for use with MCU-100J /200J JVC, (8 pin & LAN-C)	70 538 Ft
Datavideo	AD-2P	Multi transmission adapterbox for Panasonic Camera's	179 550 Ft
Datavideo	AD-2S	Multi transmission adapterbox for Sony Camera's	179 550 Ft
Datavideo	AD-2J	Multi transmission adapterbox for JVC Camera's	179 550 Ft
Datavideo	SLD-1	Shoulder Mount Rig with; Power supply from V-mount battery; USB port for LED light and Phone charger; Power Input: V-mount battery plate; Power Output: D-Tap Connector; Phone Charger and Light: USB; Dimension: 351.2 x 70 x 200.5mm	89 775 Ft
Datavideo	HP-3	Headset with 5-pin XLR (Spare for AD-2)	21 546 Ft
Datavideo	RMC-230	MCU-100&200P/S external T-Bar Box. To be used with Sony camera's only	102 600 Ft
Recorders			
Datavideo	DN-60A	Extremely Portable and Shockproof Solid State HDV/ DV Recorder. 2.5 hrs recording on 32GB CF Card (Not Supplied) - IEEE1394 I/O File support includes AVI, MOV and M2T format, DN-60 can store HDV, DV, DVCPro 25&50 signal formats. DN-60A can also be controlled by RMC-200 and for use with TLM-43LB monitor	140 819 Ft
Datavideo	DN-600	Desktop DV & HDV Harddrive recorder, with removeable 2.5" HDD (HDD not included) Digital IEEE1394 DV/ HDV input and analogue Cvbs video + RCA audio input Headphone connector. Audiolevel indicators.	338 580 Ft
Datavideo	DN-700	Rackmountable DV & HDV Harddrive recorder, with removeable 2.5" HDD (HDD not included) Digital IEEE1394 DV/ HDV input and analogue Cvbs video + RCA audio input Headphone connector. Audiolevel indicators.	338 580 Ft
Datavideo	HDR-10	Compact Highlight/Events recorder. HD/ SD Harddrive Replay recorder with removable 2.5" SSD drive (SSD not included)	371 925 Ft
Datavideo	RMC-400	Remote controller to control up to 4 HDR-10 instant replay recorders Provides a GPI interface for functions such as Switcher trigger for playback T-bar for smooth variable replay speed adjustment <i>Jog/shuttle all at once or independent! search control</i>	127 994 Ft
Datavideo	SH-1	Shuttle Express Jog/Shuttle control to operate HDR-10. FOR FREE DURING INTRODUCTION (1/HDR-10)	19 238 Ft
Datavideo	HDR-60	HD/ SD Harddrive desktop recorder with removable 2.5" HDD (SSD/ HDD not included) Video input: HD/ SD-SDI. Time code in- and output. Video output: HD/ SD SDI, HDMI. File System NTFS File formats: .MXF and .MOV Recording format 4:2:2 / Up to a max bitrate of 125 Mbps	507 870 Ft
Datavideo	HDR-70	HD/ SD Harddrive recorder with removable 2.5" HDD (SSD/ HDD not included) Video input: HD/SD-SDI, Time code in- and output. Video output: HD/SD SDI, HDMI. File System NTFS File formats: .MXF and .MOV Recording format 4:2:2 / Up to a max. bitrate of 125 Mbps, Rackmountable (1RU)	507 870 Ft
Field Monitoring - Rec/PB			
Datavideo	HRS-30	Field Recorder/Monitor supporting: HD/SD-SDI Input and Output with loop thru and embedded audio support The HRS-30 supports MPEG-II Long-GOP or I-frame only with 4:2:2 sampling Supported file formats: MXF/OP1A, MOV Quicktime Storage by a removable hard drive and compatible with 2.5" HDD & SSD drives. Internal colour bar, Blue only, Audio indicator, Safe area and time code display on a 10.1" built in monitor Can be powered by battery on the equipped V-mount adapter	705 375 Ft
Datavideo	NVP-20	Network Controllable Media Player Excellent image quality with the H.264 codec supporting:mp4, H.264, mkv, mov, TS Full HD through HDMI Output, also CVBS output is available Ethernet controllable player with control for play next clip, play all clips, loop play all clips, pause, resume and seek also remote upload of playlists is supported Supports NTFS and FAT/FAT32 formatted USB storage	96 188 Ft
Datavideo	BH-08	Small size Ball & Socket Head to mount DN-60 onto a hot shoe (camera) or BR-01 Bracket	4 232 Ft
Datavideo	BR-01	Aluminium bracket with hotshoe and tripod connector . Can hold two BH-08 for DN-60 and/ or TLM-430	9 619 Ft
Datavideo	SATA-50025	HDD 500 Gb 2.5" Sata drive, 7200 RPM 16 Mb Cache. For HDR-60/70 , DN-600/ 700 etc.	27 959 Ft

	HE-1	Spare hardrive carrier for HDR 60 -70 , DN-600-700 etc. Incl. HE-1 BAG (FOC) (HDD not included)	12 825 Ft
Datavideo	HE-1 BAG	Spare carry case for HE-1 hardrive carrier.	1 539 Ft
Datavideo	HE-2	Spare SSD carrier for HRS-30	8 978 Ft

Encoders/Decoders/Servers

Datavideo	NVS-25	Video Streaming Encoder/Server or Recorder with: H.264/AVC codec up to High Profile Level 4.0, GOP structure: IBBP, IPPP and IBP HD/SD-SDI & HDMI & CVBS Input Built in de-interlacer for progressive output DHCP Client, RTSP over TCP/UDP/HTTP with MPEG TS. RTMP, HLS (unicast only) H.264 RECORDING FUNCTION onto USB pen drive (up-to 1TB storage) @max 3Mb/s	205 200 Ft
Datavideo	NVD-20	Low Latency IP Video Decoder with: H.264 decoding, RTP/RTSP, RTMP, UDP, TCP, HTTP, HLS and MPEG-TS HDMI and Composite video Outputs Simultaneous digital embedded and analogue audio Output Channellist download from DV Stream Server Pro Channel select and volume control	96 188 Ft
	NVD-25	Low Latency IP Video Decoder with: H.264 decoding, RTP/RTSP, RTMP, UDP, TCP, HTTP, HLS and MPEG-TS SDI and Composite video Outputs Simultaneous digital embedded and analogue audio Output Channellist download from DV Stream Server Pro Channel select and volume control	166 725 Ft
Datavideo	DVS-100	DVS-100 Stream Server Software. For use with your own internal server or 3rd party cloud server. Allows Datavideo NVS encoder & NVD decoder units to be connected together easily from anywhere in the world. Connect multiple decoders to one encoder. Provides RTMP & HLS streams for playback in VLC and other players. Simple low cost CDN solution. ****FREE OF CHARGE DOWNLOAD****	- Ft
Datavideo	DVS-100Pro	Licensed DVS-100 system adding the following features: Auto/manual record of streams. Video on Demand. Channel list is automatically published to NVD decoder units enabling IPTV functionality. Embedded Video Player compatible with OSX, Windows, IOS and Android. Restrict viewing of certain channels to registered account holders (facility for Pay Per View)Per instance license (i.e. per Cloud or Local server)	76 694 Ft

Wireless Video

Datavideo	NVW-150	High Power WiFi bridging unit. The NVW-150 is a camera top solution, powered either by the supplied PSU or via optional POE Injector, or by battery. User can connect to any network enabled device via ethernet to the NVW-150 BRIDGE, which can then link to a second NVW-150 or NVW-250 DUO unit via a long range, completely transparent WiFi connection. Range appr. 250 meter with supplied antennae. Further with optional antennae.	128 250 Ft
Datavideo	NVW-250	Dual Radio high power Wi Fi bridging unit. Similar to the NVW-150. The NVW-250 DUO features a second WiFi radio allowing both long range connectivity to another NVW-250/DUO unit as well as local connection of devices via WiFi (up to 100m) or via ethernet. The NVW-250 BRIDGE DUO can exclusive be powered by a standardized V-mount battery (battery not included). The NVW-250 BRIDGE DUO comes in ruggedized case.	224 438 Ft

Prompters

Datavideo	DVP-100	Wireless teleprompting system to centrally control and synchronise multiple prompter screens through a dedicated WiFi hotspot. (iOS App: DVPrompter Pro) Not yet available for Android. UP to 6 devices can be controlled simultaneously. Controller can create and load new scripts., control the scrolling and perform live edits on all prompter screens in real time. All scripts and settings are stored on the dv prompter server. built in Dualband WiFi.	121 838 Ft
Datavideo	TP-150	Teleprompter, undercamera prompter for use with PTZ camera's holds most tablets even up to iPad pro (large version), available May 2016	38 219 Ft
Datavideo	TP-300	TP-300 Universal Prompter suitable for most camcorders and Tablets from 7" -10" W/O REMOTE Tablet can be mounted either in the traditional way using the included camera and tripod support rails, hood and beam splitter glass, or under the lens for use with retro-reflective light. Suitable for most cameras. W/O remote control for text scroll speed , next chapter etc. Datavideo iPrompter software is avaiable as free download App store REMOTE CONTROL NOT INLCLUDED Choose a Wired, wireless or Bluetooth option	102 344 Ft
Datavideo	TP-500	TP-500 7"/ DSLR Prompter W/O Remote control 18 mm Rail Adjustable Mounting system included- ideal for DSLR Camera's Adjustable mount to hold Android & Apple tablets from 7" to 10" Tablet can also mounted under the lens for use with retro reflective light. REMOTE CONTROL NOT INLCLUDED Choose a Wired, wireless or Bluetooth option	115 169 Ft
Datavideo	TP-600	TP-600 ENG Prompter in giftbox W/O remote control Larger frame Glass and mount. Suitable for ENG type cameras Adjustable mount to hold Android & Apple tablets from 7" to 10" Tablet can also mounted under the lens for use with retro reflective light. REMOTE CONTROL NOT INLCLUDED Choose a Wired, wireless or Bluetooth option	140 819 Ft
Datavideo	WR-500	WR-500 universal Bluetooth Remote Control for Telerprompter. Bluetooth 4.0 can be used also in wired mode. Suitable for Apple devices , most Android tablets & Smartphones AVAILABLE MARCH 2016	38 475 Ft
Datavideo	FS-200	FS-200 Footswitch Bluetooth 2.0 Provides start/stop function.	12 825 Ft
Datavideo	HC-300	HC-300 Water/Dust resistant High Impact Case includes Precut Diced Foam- Also suitable for TP-300 Ext. 430x380x154mm Int. 395x320x117mm with pick&pluck foam for use with other equipment	28 215 Ft

Datavideo	HC-500	HC-500 Water/Dust resistant High Impact Case includes Precut Diced Foam- Also suitable for TP-500 with pick&pluck foam for use with other equipment	19 238 Ft
Datavideo	HC-600	HC-600 Water/Dust resistant High Impact Case includes Precut Diced Foam- Also suitable for TP-600 Ext. 515x415x200mm Int. 485x355x186mm with pick&pluck foam for use with other equipment	35 910 Ft
Datavideo	TP-300GLS	Glass replacement for TP-200/300	25 394 Ft
Datavideo	TP-500GLS	Glass replacement for TP-500	20 264 Ft
Datavideo	TP-600GLS	Glass replacement for TP-600	35 654 Ft
Datavideo	CC-100	Camera Cloth replacment for TP-200 /300	8 978 Ft

Intercom Systems

Datavideo	ITC-100	Intercom/ talkback system (max. 8 ch). Includes base station, gooseneck mic. and light for base station, 4x ITC100 SL Belt Pack (see ITC-100 SL for more details)	282 150 Ft
Datavideo	ITC-100HP1-4	Intercom/talkback system as 2205-2000 but including 4 pcs. HP-1E headsets	362 178 Ft
Datavideo	ITC-100SL	Additional Belt pack kit for ITC-100. Contains: 1x ITC-100SL Beltpack, 1x TD-3 tally light, 1x CB-7 1.2 M tally cable, 1x MC-1 Microphone headset, 1x CB-3 20 meter Intercom cable 1x CB-17	51 300 Ft
Datavideo	MC-1	Standard One Ear Headphone with mic. for ITC-100SL.	3 078 Ft
Datavideo	HP-1E	Heavy Duty Professional One Ear Headphone with microphone. HP-1E does have one 3,5 mm jack for Mic & Ear to fit into beltack or ITC-100 base station	20 007 Ft
Datavideo	HP-2A	Heavy Duty Professional Two Ear Headphone with microphone. HP-2A does have one 3,5 mm jack for Mic & Ear to fit into beltack or ITC-100 base station	30 780 Ft
Datavideo	CB-17	3,5 mm jack to Headphone / Mic adapter. To use a standard (non usb) Skype headset with microphone with ITC-100 SL Beltpack	1 026 Ft
Datavideo	CB-28	SE-2800 Intercom/ Tally cable (Also for SE-2200)	6 413 Ft
Datavideo	CB-29	SE-3000 Intercom/ Tally cable	11 543 Ft
Datavideo	CB-42	Tally cable (male to Female) for SE500/600/900 15 pin	1 667 Ft
Datavideo	CB-59	SE-700/1200 Intercom/ Tally cable	3 848 Ft
Datavideo	LP-1	XLR Gooseneck light for ITC-100.	14 108 Ft
Datavideo	MC-2	XLR Gooseneck microphone for ITC-100.	17 699 Ft
	TB-20	Tally Box TB-20. Passive junction box for easy connection of tally output of Panasonic Switchers (1x 25 Pin Sub D) to Datavideo ITC-100 / ITC-200 tally interface (2x 15 Pin Sub-D) 2x 15-15 pin cable for connection between TB-20 and ITC-100 / ITC-200 included	32 063 Ft
Datavideo	TD-3	Tally Light Bi color (Red/Green) Only in combination with ITC-100 Package contains; 4x TD-3; 4x CB-7 (GPI Cable); 4x Mounting straps Set of 4	23 085 Ft

Character Generators

Datavideo	PPT-100	IEEE1394/ VGA to SDI / DV Scan Conversion software Ideal solution for PowerPoint & similar using DV Mixer such as SE-800	51 300 Ft
Datavideo	CG-250	CG-250HD HD-SD Character generator software.	126 968 Ft
Datavideo	TC&CG-200	HD/SD Character Generator Kit - Title Creator 200 Interface with CG-200 software HD CG system for mobile broadcasting, live conferences and dynamic video presentations. Works on standard Windows laptop or pc with HDMI interface. Supports vision mixers with and without DSK. No additional PCI -SDI adapter card required. Supports DSK function via HDMI or SDI overlay with optional TC-200. Supports HD video with 1080i 50/ 59,94/ 60 and 720P50 /59,94/ 60 and SD Video 576i/ 480i s Supports all Windows fonts. Compatible with Windows 7/ 8 (including CG-200 SOFTWARE)	179 550 Ft
	CG-350	HD & SD SDI Character Generator Software for live text using HD-SD SDI overlay input facility. The CG-350 is Windows-based character generators designed for live production and post production. Also suitable for Arabic text. Text direction can be changed. Will work with BMD Decklink or AJA Xena card, as a downstream keyer or as key and fill sources (depending on the card). Dynamic lower thirds 32 Bit color and animated text layers. WINDOWS ONLY Auto-updating text fields, live time clock and program-independent banner crawls (CG-350 only) Softwarekey by Dongle.	448 875 Ft
Datavideo	CG-500	CG-500 SD/HD Advanced TimeLine based CG for live / post production Real time graphic render, supports flexible play control of multiple playlists, realtime multi-layer play at the same time. WINDOWS ONLY compatible with Decklink Extreme 3D + card This is a broadcast-standard titling programme, with high class templates,IPTV to AV presentations external data support and GPU-rendered effects. It's suitable for everything from webstreaming and Live TV.	705 375 Ft

Character Generators ('Turn-key')

Datavideo	CG-350 STUDIO	CG-350 HD/SD Live CG Turnkey system, fully configured in Desktop PC and ready to go. Datavideo CG-350 software preloaded INCLUDING DONGLE (item 2400-1050) HP hardware, 1Year Warranty. Fitted with Blackmagic Decklink Extreme 4K Optional available HP Monitor LE-2202 see (code 2800-0500)	1 346 625 Ft
Datavideo	CG-350 STUDIO (2U)	CG-350 HD/SD Live CG Turnkey system, fully configured in 2U rackmount PC and ready to go. Datavideo CG-350 software preloaded INCLUDING DONGLE (item 2400-1050) HP hardware, 1Year Warranty. Fitted with Blackmagic Decklink Extreme 4K Optional available HP Monitor LE-2202 see (code 2800-0500)	1 526 175 Ft
Datavideo	CG-500 STUDIO	CG-500 HD/SD Live CG Turnkey system, fully configured and ready to go. Datavideo CG-500 software preloaded INCLUDING DONGLE (item 2400-1060) HP hardware, 1Year Warranty. Fitted with Blackmagic Decklink Extreme 4K Optional available HP Monitor LE-2202 see (code 2800-0500)HP Computers are shipped under full HP 3-3-3 International warranty. Blackmagic covered by BMD	2 116 125 Ft
Datavideo	RKM-Z230	2U RackMount kit for Z230 workstation	83 363 Ft
Datavideo	HP-LE2202	HP 21.5" LED Backlit LCD Monitor 1920 x 1080 VGA/DVI-D Fit with HP PC.	101 318 Ft

Chroma Keying

Datavideo	DVK-200	2 Input (1 Camera + 1 Background) Chromakeyer (DVI, YUV, Y-C, & CV Connections) Output signal is S-Video & Cvbs. Key on Blue / Green or Luminance RS-232 Control. Brightness, Contrast, Saturation & Tint (NTSC Only) adjustment. NTSC / PAL switchable	359 100 Ft
Datavideo	DVK-300HD	A real-time HD Chroma key and Luma key solution for any live virtual production. DVK-300HD is an advanced HD/SD chroma key device. It is easy to operate, and delivers excellent results with minimal user input required. The device can be controlled locally using a directly attached laptop or remotely over an IP-network. Support 3G-SDI / 1080P Foreground supports 3G-SDI ,HD/SD SDI , HDMI (1.4) Background supports 3G-SDI .HD/SD SDI, DVI-I Main output can be 2 SDI output simultaneously and HDMI output	461 700 Ft
Datavideo	G09220428051	Extended lens adapter 58 to 72 mm. For example for fitting a LD-1/72 onto CANON GL-2 Camera	11 543 Ft
Datavideo	G09220428021	Lensadapter 82 -72 mm (note: risk of vignetting at full wide angle-mode)	7 439 Ft
Datavideo	G09220428031	Lensadapter 58-72 mm	4 874 Ft
Datavideo	350900246	Green cotton Chromakey Fabric. Size 3 x 4 meter. Washable	20 264 Ft
Datavideo	350900346	Green cotton Chromakey fabric. Size 3 x 6 meter. Washable.	25 394 Ft
Datavideo	FT-901 Stand	Background stand for use with Reflection Fabric (Green/Blue screen) comprising 2x tripods and 1 cross bar Maximum height 2.70 meter Maximum width 3.00 meter	45 914 Ft

Virtual Studio (Trackless)

Datavideo	TVS-1000	Trackless Virtual Studio System, Turn-key solution with: Easy to use Multi-language user interface with up to 3 screens preview/multiviewer/UI Built in Character Generator, 2 Downstream keyers, 2 Clip players, still store and audio mixing Internal recorder highly-efficient H.264 and MPEG 2 recording format 1x HDMI input / output (no Tally control) w. optional Aux input Supports direct streaming to Adobe Flash encoder, Ustream and Livestream PC including Software and remote control RMC220.	1 539 000 Ft
Datavideo	TVS-1200	Trackless Virtual Studio System, Turn-key solution with: Easy to use Multi-language user interface with up to 3 screens preview/multiviewer/UI Built in Character Generator, 2 Downstream keyers, 2 Clip players, still store and audio mixing Internal recorder highly-efficient H.264 and MPEG 2 recording format Dual channel trackless virtual studio with HD-SDI in-and outputs An optional Aux input can be added. Supports direct streaming to Adobe Flash encoder, Ustream and Livestream PC including Software and remote control RMC220.	2 180 250 Ft
Datavideo	TVS-AUX	Aux input board (incl. PGM out HDMI) for extra HDMI input without Chroma Keyer. Special developed for TVS-1000/1200 (HDMI)	218 025 Ft
Datavideo	MAT-2	Green Color mat for Chroma Keying 1.8 meter * 27 meter	205 200 Ft
Datavideo	MAT-2M	Green Color mat for Chroma Keying 1.8 meter wide and XX meter long. This item can be ordered per meter.	7 567 Ft
Datavideo	TA-1	Green Color Tape 48mm * 25 Mtr.	5 130 Ft
Datavideo	PLK-400	PLK-400 Chromakey Lightkit. comprising 3X 308 LED Daylight with softbox for Background and 1x 160 LED Bicolor light with Softbox for talent . 4 x Mains powersupply, 4x Lighting stands. Supplied in wheeled hardcase with custom cut foam. Lights can run off Sony NP-F type and supplied with hotshoe adapters. Filters, diffuser, blue, magenta. Adapters for Panasonic battery (CGR-D series) Battery box for 6 AA batteries.	332 168 Ft
Datavideo	PLK-300	PLK-300 Portable light kit. Comprising of 3X 308 LED Bi Colour Lights. 3 X Light stands. Can be powered by Sony NP-F, Panasonic CG-D or AA Batteries. Batteries and main PSU are not included. Supplied in Wheeled hard case with custom cut foam.	255 218 Ft

Waveforms

Datavideo	VS-100	Waveform Vectorscope Monitor, Parade, Histogram, Video in thumbnails. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. Output resolution 1280*720. Rotary control though OSD interface.	203 918 Ft
Datavideo	VS-150	1RU Waveform Vectorscope Monitor, Parade, Histogram, Video in thumbnails. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. Output resolution 1280*720. Front panel control though OSD interface. (Optional rackmounts available RMK-1)	256 500 Ft
Datavideo	VSM-100	2RU Waveform Vectorscope Monitor with 2 monitors (4,3") providing Parade, Histogram, Video. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. With front panel control. Viewing Angle Vert.40 Deg, Hor.60 Deg HDMI and SDI outputs (loop thru's)	538 650 Ft
Datavideo	VSM-200	Dual Channel 2RU Waveform Vectorscope Monitor with 2 monitors (4,3") providing Parade, Histogram, Video. Aquisition and display; single line, single field and whole frame. HD/SD-SDI input/HDMI HD/SD SDI output with tone generator. With front panel control. Viewing Angle Vert.40 Deg, Hor.60 Deg HDMI and SDI outputs (loop thru's)	795 150 Ft

Audio mixers

Datavideo	AD-200	1U Audio mixer, level adjustment and audio delaybox. The matrix type audio mapping function allows combinaiton of multiple audio input channels into one or more output channels. Up to 3 seconds audio delay is available to synchronize audio with video. 6 XLR audio channels input. Support 2 audio input modes, Mic and Line. 2 audio modes mono / stereo.	228 285 Ft
------------------	---------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------

Datavideo	AD-100M	Audio delay box with voice over functionality. Features Microphone input, RCA (phono) connector as well as XLR connectors. Max delay: 700 ms 1U size. 19" rackmount kit as option available.	117 990 Ft
Datavideo	AM-100	19 inch rackmount audiomixer. 1U A 6 channel (4x mono+ 1x stereo input) audiomixer. Supports line and mic. level for Ch.1- Ch.4 48V Phantom power (on/ off) for Ch.1- Ch.4 Separate gain and level adjustment per channel	153 900 Ft
LCD Monitors			
Datavideo	TLM-170GR	TFT LCD Monitor 7U Rackmount, 17,3" (1600x900), HD/SD-SDI inputs with loop thru and 2x HDMI input, mono analogue audio input, built in speakers for listening to every source (De-embed function), Bi-color tally, built in audio monitoring (visual OSD), built in TPG, Aspect marker & source identification (OSD)	410 400 Ft
Datavideo	TLM-170G	TFT LCD Monitor Desktop, 17,3" (1600x900), HD/SD-SDI inputs with loop thru and 2x HDMI input, mono analogue audio input, built in speakers for listening to every source (De-embed function), Bi-color tally, built in audio monitoring (visual OSD), built in TPG, Aspect marker & source identification (OSD)	384 750 Ft
Datavideo	TLM-170GM	TFT LCD Monitor 1U Foldable Racktray, 17,3" (1600x900), HD/SD-SDI inputs with loop thru and 2x HDMI input, mono analogue audio input, built in speakers for listening to every source (De-embed function), Bi-color tally, built in audio monitoring (visual OSD), built in TPG, Aspect marker & source identification (OSD)	500 175 Ft
Datavideo	TLM-170P	17,3" LED Backlight Desktop monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. CVBS video input with loopthrough output. On Screen Time code display. Underscan- overscan. Safe Area indication. Adjustable Color temperature . Supports embedded audio.	513 000 Ft
Datavideo	TLM-170PM	17,3" LED Backlight 1U Foldable Racktray monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. CVBS video input with loopthrough output. On Screen Time code display. Underscan- overscan. Safe Area indication. Adjustable Color temperature . Supports embedded audio.	615 600 Ft
Datavideo	TLM-170PR	17,3" LED Backlight 7U Rackmount monitor 1920x1080P Panel resolution. Support 3Gbps/HD/SD-SDI input with loop through. CVBS video input with loopthrough output. On Screen Time code display. Underscan- overscan. Safe Area indication. Adjustable Color temperature . Supports embedded audio.	525 825 Ft
Datavideo	TLM-433	High Quality 3x 4,3", 16:9 ratio LCD/TFT monitor system. 4:3 ratio compatible. Panel resolution 480x270 pixels. View angle =(V)+40/-60, (H)+60/-60 degrees. Auto PAL/ NTSC detection. Individual adjustments for brightness, contrast, colour, tint (NTSC). 3x Composite video in (loop through). 2 Colour tally system. 19" Rackmountable, 2U High. Can be tilted +/- 30 degrees. 12V dc input. 110-240V ac adapter included.	256 500 Ft
Datavideo	TLM-434H	High Quality 4x 4,3", 16:9 ratio LCD/TFT monitor system. 4:3 ratio compatible. Screen Resolution: 480 x 272 pixels Input: HD/SD SDI, HDMI. Output:HD/SD SDI loop through 12V dc input. 110-240V ac adapter included.	641 250 Ft
Datavideo	TLM-430	4.3" LCD Look Back Monitor, with enlarged BI Color Tally light. Two Cvbs video inputs: one for camera and one for return (live) feed from switcher Resolution 480x272 LCD, active matrix. CB-26 Breakout cable for lookback is optional available. 2200-9892 Supports both 16:9 & 4:3 aspect ratio. DC 6V power operation via AC adapter (incl.) or Sony BP-U / NP-F series battery (not incl.) Remote controllable by Datavideo RMC-200	84 645 Ft
Datavideo	TLM-43LB	Kit of Look Back Monitor, Controller, Bracket & BH-08 Comprises: TLM-430 Look Back Monitor Bracket to mount Monitor & Datavideo DN-60(A) via Camera Hot Shoe RMC-200 Camera Remote Controller BH-08 Ball head CB-15U - 90 degree DV cable CB-26 Breakout cable	107 730 Ft
Datavideo	TLM-700HD	High res. 7", 16:9 LCD/TFT monitor. 4:3 ratio compatible. Panel resolution: 800x480Pixels. HD/SD-SDI, (HD-)YUV, CV and HDMI input. Standard V-mount enabeling powering up with universal battery for in the field use. Audio indicator for SDI & HDMI . Safe area indicator	166 469 Ft
Datavideo	TLM-700HD-A	High res. 7", 16:9 ratio LCD/TFT monitor. Anton Bauer battery mount	205 200 Ft
Datavideo	TLM-700HD-C	High res. 7", 16:9 ratio LCD/TFT monitor. Canon BP-9xx battery mount	205 200 Ft
Datavideo	TLM-700HD-S1	High res. 7", 16:9 ratio LCD/TFT monitor Sony BP-Ux battery mount (like EX-1, EX-3)	205 200 Ft
Datavideo	TLM-700HD-S2	High res. 7", 16:9 LCD/TFT monitor Sony NP-Fxxx battery mount (like Z5)	205 200 Ft
Datavideo	TLM-700HD-P	High res. 7", 16:9 ratio LCD/TFT monitor. Panasonic CGA battery mount	205 200 Ft
Datavideo	TLM-702	2x 7" 16:9 Wide Screen Monitors in 19" Rack Mount with 90 degree tilt Auto PAL/ NTSC. 2 colour tally light. Individual control for contrast, brightness, colour Video Loop through. 12v DC / 240v AC. 30 day Guaranteed against spot light defect.	218 025 Ft
Datavideo	TLM-702HD	2 x 7" 16:9 Wide Screen Monitors in 19" Rack Mount with 90 degree tilt Blue Only Function, Brightness, Contrast & Colour Adjustment (& Tint NTSC only). Colour Bars NTSC/PAL Auto Switching. Audio level Indicators . HD/SD-SDI, YUV, CV, HDMI & Tally Input. Headphone output. DC Input via 12v PSU (Supplied).	280 868 Ft
Datavideo	G13304581201-AUO	SDI Module for TLM-170 and TLM-170M contact office for compatibility	76 950 Ft
Datavideo	G09220566011	EarRack for TLM-170H incl. screws	29 498 Ft
Datavideo	TLM-433JF	Universal Desktop Stand / Holder suitable for: SE-800 + TLM-404 & TLM-702 (or single monitor) with or without ITC-100 SE-1000 + 1 or 2 x TLM-433 with or without ITC-100	43 349 Ft
Datavideo	RMK-1	Rack Mount Kit for one or two 1U height products, such as VSM -150 Vector scope Half 19 inch rack mount unit: 2 x Rack Ear 1x Rack Panel (1U) 4x M4*8 screw Note: Not suitable for AD-100!	12 825 Ft
Datavideo	RMC-200	Remote control for TLM-430 lookback monitor, to switch between ACTUAL and CAMERA Monitor function. For use in combination with CB 23 -24 All-in One Cable Includes Control-L/ Lanc connector for simple start stop and zoom function. This function is not available on all Sony Camera's	30 780 Ft
Datavideo	CB-26	CB-26 Breakout cable TLM-43LB	11 543 Ft

Signal Converters

Datavideo	DAC-7	Analog to SD-SDI video converter with CVBS/S-Video/YUV inputs. Also audio inputs are available for embedding purposes.	89 775 Ft
Datavideo	DAC-8P	HD/SD-SDI to HDMI converter & audio demux (1080P) Can be used for connecting the HD-SDI PGM out of a switcher to a projector with HDMI in.	75 668 Ft
Datavideo	DAC-9P	HDMI HD-Video to HD/SD-SDI Converter (1080P) also embeds audio from HDMI signal into HD-SDI signal. Supported input formats: 480i, 576i, 720P50/ 59,94/ 60, 1080i50/ 59,94/ 60 and 1080P50/ 59,94/ 60	75 668 Ft
Datavideo	DAC-50S	HD-SDI to SD analog video converter. Available outputs: YUV/S-Video(YC) / 2x CVBS (Supports PAL&NTSC)	89 519 Ft
Datavideo	DAC-60	HD/ SD-SDI to VGA converter. Supported HD input formats: 720P50/ 60, 1080i50/ 60 and 1080P24/ 25/ 30/ 50/60 Supported SD input formats: 525i (NTSC) and 625i (PAL) Supported VGA output formats (all at 60Hz): 800x600, 1024x768, 1280x800, 1280x1024, 1366x 768, 1400x1050, 1600x1200, 1920x1080, 1920x1200 (Firmware version V0.1.1.0 required)	89 775 Ft
Datavideo	DAC-70	Multi format up /down /cross converter "Many formats in (auto detect) to many formats out (by dipswitch selection)" Input connectors: VGA (up to 1600x1200), HDMI-video , (HD-)SDI and RCA audio. Output connectors: HDMI and 2x (HD) SDI. Video output formats: 480/576i, 720P50/59,94/60, 1080i50/ 59,94/60, 1080P23,98/24/25/50/60 The DAC-70 supports HDCP for HDMI input. Supports multi-channel audio (SDI / HDMI 8 ch audio embedded)	127 994 Ft
Datavideo	DAC-80	DAC-80 / 2 Channel Audio 1:1 transformer High quality ground loop isolator (with ground lift) to avoid audio hum XLR in / out	28 215 Ft
Datavideo	DAC-90	3Gbps/HD/SD-SDI Audio de-embedder, 4 Analog mini XLR audio outputs. Each set of channels can be selected with the dipswitches (selection of group 1-4) Incl. 2 mini XLR 'pigtailes'	76 694 Ft
Datavideo	DAC-91	3Gbps/HD/SD Analogue audio embedder, embedding 2 channels of analog audio into SDI video signal. Automatically detects 3G,HD SDI signal. 2 analog inputs (Mini XLR or RCA x2) Audio level indicator display. Audio level adjustment and control via DIP switches. Including 2 mini XLR 'pigtailes'	86 954 Ft
Datavideo	RMK-2	19" 2 U rack mount holder for up to 8 x DAC Converters. Mounts up to 8 datavideo converters in a single 2U rackframe. Single power Connection Suitable for DAC-8(p), DAC-9(p) DAC-60 , DAC-70	75 668 Ft
Datavideo	MB-4-S1	DAC-series mountingbracket with Batteryholder for power support. This mounting braketr can easily connect to Tripod or other. Battery holder can support widely useded batteries and makes your DAC portable. Battery mount for SONY BP-U60, BP-U30 Compatible with Datavideo DAC series, DAC60/70, DAC8P/9P, VP-597	17 955 Ft
Datavideo	MB-4-S2	Battery mount for DAC converter compatible with SONY NP-F770/ 970/ 960/ 950	17 955 Ft
Datavideo	MB-4-P	Battery mount for DAC converter compatible with Panasonic CGA series	17 955 Ft
Datavideo	MB-4-C	Battery mount for DAC converter compatible with CANON BP series	17 955 Ft
Datavideo	MB-4-S	Battery mount for DAC converter compatible with SONY NP-QM series	17 955 Ft
Datavideo	MB-4-BB	Battery mount for DAC converter compatible withw/o battery plate	10 004 Ft
Datavideo	MB-5	DAC series Tripod mounting bracket for DAC series	6 413 Ft
Datavideo	BAC-03	Two way balanced <> unbalanced audio converter Converts phono/ RCA to XLR audio and vice versa Can be used with DAC's or SE-800 Mixer/ switcher	57 713 Ft
Datavideo	CAD-01	Balanced to Unbalanced (XLR female to RCA male) audio attenuator (-10dB) (2 pc.)	7 439 Ft
Distribution Amplifiers			
Datavideo	VP-737	Composite video repeater & transmitter (set of) wired composite transmission as far as 200 meters. Cat5e extension design make use of existing Cat5e or better wiring infrastructure.	32 063 Ft
Datavideo	VP-633	3G/HD/SD SDI Active Signal Repeater. Powered to provide power to VP-634 with re-clocking function. (Supports up to 3 passive repeaters, VP-634)	76 950 Ft
Datavideo	VP-634	3G/HD/SD SDI Passive Signal Repeater (Needs a VP-633 to operate) Provides SDI re-clocking function.	69 255 Ft
Datavideo	VP-445	1 Input/ 4 Output HD/SD-SDI Distribution Amplifier Small metal form factor with mounting brackets for easy mounting	51 044 Ft
Datavideo	VP-597	1 Input/ 6 Outputs 3G HD/SD SDI Distribution Amplifier Two input video source selection can be controlled by A/B switch or GPI Remote	76 694 Ft
Datavideo	VP-781	VP-781 HD/SD SDI +intercom repeater for use with 2 x CB-50 cables (not included) providing intercom, tally and SD/HD-SDI video runs up to 200m. Built in repeater and 5Pin XLR intercom pass through. Requires VP-633 powered SDI repeater.	73 103 Ft
Datavideo	VP-605H	Heavy Duty All-in One Cable extender with built in amplifier. Support 48V To provide SDI signal repeater , re-clock function and power delivery Typical Cable Length Performance Data Rate example Canare 5CFB cable (m) 3G-SDI at 2.97Gb/s: 100M HD-SDI at 1.485 Gb/s: 200M SD-SDI at 270 Mb/s: 300M	100 035 Ft
System Installation Gear / PSU			
Datavideo	PD-2A	PD-2A Power Distributor providing 400 Watt rated power supply to copver most power requirments.	256 500 Ft
Datavideo	PD-4A	19 inch rackmount Redundant Power Center. PD-4A Center is specifically designed to provide a steady power supply for datavideo mobile studio applications. It provides a 300 watt rated power supply to cover most power requirements for a mobile studio, such as a video switcher, LCD monitors, video recorders, talk back system, and so on. It comes with a standard 19"/1U rack size design, the PD-4 makes system integration professional and reliable. With two AC power supplies, the PD-4 will still supply energy to your devices, even if one power source fails	410 400 Ft
Datavideo	PD-5	AC Power distributor For OB-VAN rack - special production only- NOCE	205 200 Ft

Datavideo	PD-6	PD-6 is a 19" rack mountable universal AC to DC power distribution center. Designed to supply steady and sequenced voltage for production kit whilst on location or in your studio. The PD-6 supplies a steady user chosen voltage 12,14,4,24, or 48 volts. Related products for 48V are : DC/DC converter DDC-4012H code 2600-3011 CB-22 H cable 30 mtr. Code 2200-9882 CB-23 H Cable 50 mtr. Code 2200-9883	384 750 Ft
Datavideo	DDC-4012H	DC/ DC converter for use in combination with PD-6 power distribution centre and CB-22H/ 23H All in One cable related products for 48V are : PD-6 PowerCenter CB-22 H cable 30 mtr. Code 2200-9882 CB-23 H Cable 50 mtr. Code 2200-9883	44 888 Ft
Datavideo	DDC-2512	DC /DC converter for Phantom power in combination with PD-3 power distribution centre and CB-22/ 23 All in One cable Fixed 12V DC output (max 2.5A)	25 394 Ft
Rack Panels			
Datavideo	RP-11	19 inch, 3 Rackunit cover panel Can be used with MS-Series or OBV-Series products	12 825 Ft
Datavideo	RP-12	19 inch, 1 Rackunit cover panel Can be used with MS-Series or OBV-Series products	6 413 Ft
Datavideo	RP-28	Hinged Rack Tray to hold SE-900 Keyboard Requires 3 RU Can be used with MS-Series or OBV-Series products	56 430 Ft
Datavideo	RP-31	19 inch patch panel for ITC-100. 8x 5 pin XLR I/O connector for ITC-100SL Can be used with MS-Series or OBV-Series products	50 018 Ft
Datavideo	RP-34	MS-900 cable set	38 475 Ft
Datavideo	RP-45	19" Composite video distribution amplifier (1 to 8) PSU included Can be used with MS-Series or OBV-Series products	33 345 Ft
Datavideo	RP-50	19 inch, 1 Rackunit blind panel with a Euro powerconnector on the outside providing power inside a rack with a regual power socket (UK, US and Euro compatible) Can be used with MS-Series or OBV-Series products	17 955 Ft
Datavideo	RP-51	19 inch, 1 Rackunit built up of 2 half 19" components; *Left side VP-445 HD/SD distribution amplifier with connections *Right side the AD-100 with interface facing outside Can be used with MS-Series or OBV-Series products	230 850 Ft
Datavideo	RP-61	RP-61 RP-ONE U (blank panel) universal Neutrik connector panel.	23 085 Ft
Datavideo	RP-64	VIDEO BUFFER and HD-SDI to analog converter rear panel	128 250 Ft
Datavideo	RP-BRIDGE	RP-BRIDGE rear panel for SDI input	102 600 Ft
Datavideo	PP-ONE X	Rear panel for SDI output + power out	153 900 Ft
Datavideo	PP-ONE D	Rearpanel for SDI connector	71 820 Ft
Datavideo	PP-BASE	Base plate OBV 2800	106 448 Ft
Datavideo	OBV base V	Base plate for Rack fit Mercedes Viano	230 850 Ft
Datavideo	PP-3U-cover	3U cover plate for OBV	3 591 Ft
Datavideo	PP-Cover	Cover plate for Cabling OBV	19 238 Ft
HDMI Peripherals			
Datavideo	PP-ONE E	Rear panel for 3 pin XLR +HDMI connector	70 538 Ft
Datavideo	PP-ONE Z	Rearpanel for HDMI connector and power in	102 600 Ft
Datavideo	RP-52	19 inch, 1 Rackunit with 2 XLR connectors and 3 HDMI connectors Can be used with MS-Series or OBV-Series products	96 188 Ft
Datavideo	RP-62	HD/SD HDMI Ditribution with ITC-100 breakout panel	157 748 Ft
Datavideo	CB-20	DVI <-> HDMI Cable black 1.8 mtr.	4 874 Ft
Datavideo	CB-60	HDMI Active Optical Cable with High performance. 30 meter. Can transmit 4K@60Hz UHD up to more than 100 mtr. Support HDMI 2.0, Support HDCP 2.2. Plug and Play. Highly resistant with EMI and RFI. No external power needed.	93 623 Ft
Datavideo	CB-61	HDMI Active Optical Cable with High performance. 50 meter. Can transmit 4K@60Hz UHD up to more than 100 mtr. Support HDMI 2.0, Support HDCP 2.2. Plug and Play. Highly resistant with EMI and RFI. No external power needed.	121 838 Ft
Datavideo	CB-62	HDMI Active Optical Cable with High performance. 100 meter. Can transmit 4K@60Hz UHD up to more than 100 mtr. Support HDMI 2.0, Support HDCP 2.2. Plug and Play. Highly resistant with EMI and RFI. No external power needed.	179 550 Ft
Cables			
Datavideo	DVM-2264	IEEE1394 / DV Firewire Cable 1.8M (6P-4P) 400mbps	3 078 Ft
Datavideo	DVM-2266	IEEE1394 / DV Firewire Cable 1.8M (6P-6P) 400mbps	3 078 Ft
Datavideo	DVM-2066	High Quality 20M IEEE1394/DV Cable. 6 Pin- 6 Pin (6P-4P Adapt available) 200mbps. Suitable for all DV / DVCAM.	19 238 Ft
Datavideo	CB-2	To convert S-video connector with lock to 2 BNC connectors Usefull in combination with SE-500. Can transmit S-video over long distance by using two standard BNC cables. SET of 2 pcs.	3 591 Ft
Datavideo	CB-3	20m Intercom extension Cable 5 pin XLR connector for use in combination with ITC-100SL. Max. 200 mtr.	12 825 Ft
Datavideo	CB-4	50m Intercom extension Cable 5 pin XLR connector for use in combination with ITC-100SL max. 200 mtr.	26 933 Ft
Datavideo	CB-7	GPI / Tally cable 1.2 Mtr.	641 Ft
Datavideo	CB-8	3,5 mm(male) jack to 4 pin XLR (female) cable adapter for ITC-100 SL beltack	1 924 Ft
Datavideo	CB-9	DV-I Cable black 1.8 mtr. For use with SE-1000	5 771 Ft

Datavideo	CB-10	High Quality HD/ SD cable,YUV 4*BNC- 4*BNC, length 3Mtr. Made by Canare (Japan)	19 238 Ft
Datavideo	CB-14	High Quality SD cable,YUV 4*BNC-4*BNC, lenght 3Mtr. Made by Canare (Japan)	7 695 Ft
Datavideo	CB-15U	DV cable with 6 pin FireWire connector in 90 degrees upright position. Very usefull cable for use with all HDD recorders as it will reduce the downforce on the connector lenght about 20	3 848 Ft
Datavideo	CB-15D	DV cable with 6 pin FireWire connector in 90 degrees down right position. Very usefull tool for use with all HDD recorders as it will reduce the downforce on the connector lenght about 20	3 848 Ft
Datavideo	CB-19	DVI-D <-> DVI-D Cable black 1.8 mtr.	5 643 Ft
Datavideo	CB-22H	All-in One features: 1x 4 pin XLR power cable, 1x5 pin XLR Intercom, 1x BNC for Video, 1x BNC for return Length: 30 meter Related products for 48V are : PD-6 PowerCenter (2205-1060) DC/DC converter DDC-4012H (2600-3011) VP-605H heavy duty cable extender (2332-2010)	69 255 Ft
Datavideo	CB-23H	All-in One features: 1x 4 pin XLR power cable, 1x5 pin XLR Intercom, 1x BNC for Video, 1x BNC for return Length: 50 meter Related products for 48V are : PD-6 PowerCenter (2205-1060) DC/DC converter DDC-4012H (2600-3011) VP-605H heavy duty cable extender (2332-2010)	98 753 Ft
Datavideo	CB-24	All in one cable for use with SD-SDI and Cvbs MVS systems. 18 AWG Includes connectors for Intercom & Tally, Video SD-SDI & return video for Look Back monitor Length: 100 meter	178 268 Ft
Datavideo	CB-25	RS-232 control cable for recorder DN-60	1 026 Ft
Datavideo	CB-26	CB-26 Breakout cable TLM-43LB	11 543 Ft
Datavideo	CB-30	All-in One Cable 30 meter: 1x HD/ SD SDI, 1x Cvbs for retun video 2x RJ45 connector for use icw MCU-100 and AD-1 and 5 Pin XLR for Talk back and Tally	76 950 Ft
Datavideo	CB-31	All-in One Cable 50 meter: 1x HD/ SD SDI, 1x Cvbs for retun video 2x RJ45 connector for use icw MCU-100 and AD-1 and 5 Pin XLR for Talk back and Tally	111 578 Ft
Datavideo	CB-32	Cable set for MS-2800A/B	100 035 Ft
Datavideo	CB-33	Cable set for OBV-2800	74 129 Ft
Datavideo	CB-40	Mini DIN 9 to 4* BNC	5 130 Ft
Datavideo	CB-41	Dual side audio 3-pin XLR cable	5 130 Ft
Datavideo	CB-42	D-SUB 15 pin Tally cable (male to Female) for SE500/600/900	1 667 Ft
Datavideo	CB-43	All in one cable for CCU-100 art. nr. 2205-1200 Length: 30 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	123 120 Ft
Datavideo	CB-44	All in one cable for CCU-100 art. nr. 2205-1200 , Length: 50 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	184 680 Ft
Datavideo	CB-45	All in one cable for CCU-100 art. nr. 2205-1200, Length: 80 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	256 500 Ft
Datavideo	CB-46	All-in One Cable L:30 Mtr. HD-SDI For HS series switcher. The cable includes SDI, intercom and Tally cable.	51 300 Ft
Datavideo	CB-47	All-in One Cable L:50 Mtr. HD-SDI. For HS series switcher. The cable includes SDI, intercom and Tally cable.	79 515 Ft
	CB-48	All-in One Cable L:100 Mtr. HD-SDI +Intercom To cover 100 meter HD -SDI signal we using for this cable 4.5C HD Coaxial cable All in one cable are designed for HS series switcher. The cable includes SDI, intercom and Tally cable.	211 613 Ft
Datavideo	CB-49	All in one cable for CCU-100 art. nr. 2205-1200, Length: 100 meters (17 Pin plug, connecting HD-SDI, MCU Control, Power, Look Back, Viewfinder & Intercom)	307 800 Ft
	CR-49	CR-1 including 100 meter CCU cable CB-49	384 750 Ft
Datavideo	CB-50	All in one cable 2,5C HD (100 Meter)	148 770 Ft
	CR-1	Cable Reel w/o cable	74 385 Ft
	CA-64	30cm 6P(female)-4P(male) adapter - to convert 6P fitting to 4P fitting.	3 848 Ft

Time Base Corrector

	TBC-5000	TBC & Matrix switcher Frame synchronizer 4:2:2 Multi functions with 4 TBC. 4 in -1 out synchronization video switcher, 4 in -4 out a synchronous 4 in 2 out . Combined with DVK-100 chromakeyer, user can assemble low cost dual camera virtual broadcast studio for entertainment applications. Can be mounted in 19 inch rack see bracket 2200-9530	205 200 Ft
--	-----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------

LED Flashlight

	FL-01	A must in every toolbox :-) LED Flash light, 70000 mcd, Operating 10 hours on 1 AAA sixze battery. (not included) pensize model with clip made from high density aluminium alloy. Waterproof IP 67 standard.	2 565 Ft
--	--------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------